

**STATE OF MISSISSIPPI  
AIR POLLUTION CONTROL  
TITLE V PERMIT**

**TO OPERATE AIR EMISSIONS EQUIPMENT**

**THIS CERTIFIES THAT**

Stella-Jones Corporation – Durant  
17156 Highway 51 North  
Durant, Holmes County, Mississippi

has been granted permission to operate air emissions equipment in accordance with emission limitations, monitoring requirements and conditions set forth herein. This permit is issued in accordance with Title V of the Federal Clean Air Act (42 U.S.C.A. § 7401 - 7671) and the provisions of the Mississippi Air and Water Pollution Control Law (Section 49-17-1 et. seq., Mississippi Code of 1972), and the regulations and standards adopted and promulgated thereunder.

**MISSISSIPPI ENVIRONMENTAL QUALITY PERMIT BOARD**



**AUTHORIZED SIGNATURE**

**MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY**

**Permit Issued: May 16, 2023**

**Permit No.: 1140-00063**

**Modified: January 30, 2024**

**Effective Date: As Specified Herein.**

**Expires: April 30, 2028**

## **TABLE OF CONTENTS**

SECTION 1. GENERAL CONDITIONS .....	3
SECTION 2. EMISSION POINTS & POLLUTION CONTROL DEVICES .....	14
SECTION 3. EMISSION LIMITATIONS & STANDARDS.....	15
SECTION 4. COMPLIANCE SCHEDULE.....	25
SECTION 5. MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS .....	26
SECTION 6. ALTERNATIVE OPERATING SCENARIOS.....	32
SECTION 7. TITLE VI REQUIREMENTS .....	33

### **APPENDIX A LIST OF ABBREVIATIONS USED IN THIS PERMIT**

## SECTION 1. GENERAL CONDITIONS

1.1 The permittee must comply with all conditions of this permit. Any permit non-compliance constitutes a violation of the Federal Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(6)(a).)

1.2 It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(6)(b).)

1.3 This permit and/or any part thereof may be modified, revoked, reopened, and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(6)(c).)

1.4 Prior to its expiration, this permit may be reopened in accordance with the provisions listed below.

(a) This permit shall be reopened and revised under any of the following circumstances:

(1) Additional applicable requirements under the Federal Act become applicable to a major Title V source with a remaining permit term of three (3) or more years. Such a reopening shall be completed no later than eighteen (18) months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended.

(2) Additional requirements (including excess emissions requirements) become applicable to an affected source under the acid rain program. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the permit.

(3) The Permit Board or the EPA determines that the permit contains a material mistake or that inaccurate statements were made in establishing the emission standards or other terms or conditions of the permit.

(4) The Administrator or the Permit Board determines that the permit must be

revised or revoked to assure compliance with the applicable requirements.

- (b) Proceedings to reopen and issue this permit shall follow the same procedures as apply to initial permit issuance and shall only affect those parts of the permit for which cause to reopen exists. Such reopening shall be made as expeditiously as practicable.
- (c) Re-openings shall not be initiated before a notice of such intent is provided to the Title V source by the MDEQ at least thirty (30) days in advance of the date that the permit is to be reopened, except that the Permit Board may provide a shorter time period in the case of an emergency.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.G.)

- 1.5 The permittee shall furnish to the MDEQ within a reasonable time any information the MDEQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the MDEQ copies of records required to be kept by the permittee or, for information to be confidential, the permittee shall furnish such records to the MDEQ along with a claim of confidentiality. The permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(6)(e).)

- 1.6 This permit does not convey any property rights of any sort, or any exclusive privilege.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(6)(d).)

- 1.7 The provisions of this permit are severable. If any provision of this permit or the application of any provision of this permit to any circumstances is challenged or held invalid, the validity of the remaining permit provisions and/or portions thereof or their application to other persons or sets of circumstances, shall not be affected thereby.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(5).)

- 1.8 The permittee shall pay to the MDEQ an annual permit fee. The amount of fee shall be determined each year based on the provisions of regulated pollutants for fee purposes and the fee schedule specified in the Commission on Environmental Quality's order, which shall be issued in accordance with the procedure outlined in Mississippi Administrative Code, Title 11, Part 2, Chapter 6 – “Air Emissions Operating Permit Regulations for Purposes of Title V of the Federal Clean Air Act”.

- (a) For purposes of fee assessment and collection, the permittee shall elect for actual or allowable emissions to be used in determining the annual quantity of emissions unless the Commission determines by order that the method chosen by the applicant for calculating actual emissions fails to reasonably represent actual emissions.

Actual emissions shall be calculated using emission monitoring data or direct emissions measurements for the pollutant(s); mass balance calculations such as the amounts of the pollutant(s) entering and leaving process equipment and where mass balance calculations can be supported by direct measurement of process parameters, such direct measurement data shall be supplied; published emission factors such as those relating release quantities to throughput or equipment type (e.g. air emission factors); or other approaches such as engineering calculations (e.g. estimating volatilization using published mathematical formulas) or best engineering judgments where such judgments are derived from process and/or emission data which supports the estimates of maximum actual emission.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.A.(2).)

- (b) If the Commission determines that there is not sufficient information available on a facility's emissions, the determination of the fee shall be based upon the permitted allowable emissions until such time as an adequate determination of actual emissions is made. Such determination may be made anytime within one year of the submittal of actual emissions data by the permittee.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.A.(2).)

- (c) If at any time within the year the Commission determines that the information submitted by the permittee on actual emissions is insufficient or incorrect, the permittee will be notified of the deficiencies and the adjusted fee schedule. Past due fees from the adjusted fee schedule will be paid on the next scheduled quarterly payment time.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.D.(2).)

- (d) The fee shall be due September 1 of each year. By July 1 of each year, the permittee shall submit an inventory of emissions for the previous year on which the fee is to be assessed. The permittee may elect a quarterly payment method of four (4) equal payments; notification of the election of quarterly payments must be made to the MDEQ by the first payment date of September 1. The permittee shall be liable for penalty as prescribed by State Law for failure to pay the fee or quarterly portion thereof by the date due.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.D.)

- (e) If in disagreement with the calculation or applicability of the Title V permit fee, the permittee may petition the Commission in writing for a hearing in accordance with State Law. Any disputed portion of the fee for which a hearing has been requested will not incur any penalty or interest from and after the receipt by the Commission of the hearing petition.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.C.)

1.9 No permit revision shall be required under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes for changes that are provided for in this permit.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(8).)

1.10 Any document required by this permit to be submitted to the MDEQ shall contain a certification by a responsible official that states that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.2.E.)

1.11 The permittee shall allow the MDEQ, or an authorized representative, upon the presentation of credentials and other documents as may be required by law to perform the following:

- (a) Enter upon the permittee's premises where a Title V source is located, emissions-related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
- (d) As authorized by the Federal Act, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.C.(2).)

1.12 Except as otherwise specified or limited herein, the permittee shall have necessary sampling ports and ease of accessibility for any new air pollution control equipment, obtained after May 8, 1970, and vented to the atmosphere.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.I.(1).)

1.13 Except as otherwise specified or limited herein, the permittee shall provide the necessary sampling ports and ease of accessibility when deemed necessary by the Permit Board for air pollution control equipment that was in existence prior to May 8, 1970.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.I.(2).)

- 1.14 Compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance where such applicable requirements are included and are specifically identified in the permit or where the permit contains a determination, or summary thereof, by the Permit Board that requirements specifically identified previously are not applicable to the source.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.F.(1).)

- 1.15 Nothing in this permit shall alter or affect the following:

- (a) The provisions of Section 303 of the Federal Act (emergency orders), including the authority of the Administrator under that section;
- (b) The liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance;
- (c) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Federal Act.
- (d) The ability of EPA to obtain information from a source pursuant to Section 114 of the Federal Act.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.F.(2).)

- 1.16 The permittee shall comply with the requirement to register a Risk Management Plan if permittee's facility is required pursuant to Section 112(r) of the Act to register such a plan.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.H.)

- 1.17 Expiration of this permit terminates the permittee's right to operate unless a timely and complete renewal application has been submitted. A timely application is one which is submitted at least six (6) months prior to expiration of the Title V Operating Permit (TVOP). If the permittee submits a timely and complete application, the failure to have a TVOP is not a violation of regulations until the Permit Board takes final action on the permit application. This protection shall cease to apply if, subsequent to the completeness determination, the permittee fails to submit by the deadline specified in writing by the MDEQ any additional information identified as being needed to process the application.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.C.(2)., R. 6.4.B., and R. 6.2.A.(1)(c).)

- 1.18 The permittee is authorized to make changes within their facility without requiring a permit revision (ref: Section 502(b)(10) of the Act) if:

- (a) The changes are not modifications under any provision of Title I of the Act;
- (b) The changes do not exceed the emissions allowable under this permit;
- (c) The permittee provides the Administrator and the Department with written notification in advance of the proposed changes [at least seven (7) days, or such other timeframe as provided in other regulations for emergencies] and the notification includes the following:
  - (1) A brief description of the change(s);
  - (2) The date on which the change will occur;
  - (3) Any change in emissions; and
  - (4) Any permit term or condition that is no longer applicable as a result of the change.
- (d) The permit shield shall not apply to any Section 502(b)(10) change.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.F.(1).)

- 1.19 Should the Executive Director of the MDEQ declare an Air Pollution Emergency Episode, the permittee will be required to operate in accordance with the permittee's previously approved Emissions Reduction Schedule or, in the absence of an approved schedule, with the appropriate requirements specified in Mississippi Administrative Code, Title 11, Part 2, Chapter 3 – “Regulations for the Prevention of Air Pollution Emergency Episodes” for the level of emergency declared.

(Ref.: 11 Miss. Admin. Code Pt. 2, Ch. 3.)

- 1.20 Except as otherwise provided herein, a modification of the facility may require a Permit to Construct in accordance with the provisions of Mississippi Administrative Code, Title 11, Part 2, Chapter 2 – “Permit Regulations for the Construction and/or Operation of Air Emissions Equipment”, and may require modification of this permit in accordance with Mississippi Administrative Code, Title 11, Part 2, Chapter 6 – “Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act”.

“Modification” is defined as [a]ny physical change in or change in the method of operation of a facility which increases the actual emissions or the potential uncontrolled emissions of any air pollutant subject to regulation under the Federal Act emitted into the atmosphere by that facility or which results in the emission of any air pollutant subject to regulation under the Federal Act into the atmosphere not previously emitted. A physical change or change in the method of operation shall not include:

- (a) Routine maintenance, repair, and replacement;



- (b) Use of an alternative fuel or raw material by reason of an order under Sections 2 (a) and (b) of the Federal Energy Supply and Environmental Coordination Act of 1974 (or any superseding legislation) or by reason of a natural gas curtailment plan pursuant to the Federal Power Act;
- (c) Use of an alternative fuel by reason of an order or rule under Section 125 of the Federal Act;
- (d) Use of an alternative fuel or raw material by a stationary source which:
  - (1) The source was capable of accommodating before January 6, 1975, unless such change would be prohibited under any federally enforceable permit condition which was established after January 6, 1975, pursuant to 40 CFR 52.21 or under regulations approved pursuant to 40 CFR 51, Subpart I (or 40 CFR 51.166); or
  - (2) The source is approved to use under any permit issued under 40 CFR 52.21 or under regulations approved pursuant to 40 CFR Part 51, Subpart I (or 40 CFR 51.166).
- (e) An increase in the hours of operation or in the production rate unless such change would be prohibited under any federally enforceable permit condition which was established after January 6, 1975, pursuant to 40 CFR 52.21 or under regulations approved pursuant to 40 CFR Part 51, Subpart I (or 40 CFR 51.166); or
- (f) Any change in ownership of the stationary source.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.1.C.(15).)

1.21 Any change in ownership or operational control must be approved by the Permit Board.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.D(4).)

1.22 This permit is a Federally-approved operating permit under Title V of the Federal Clean Air Act as amended in 1990. All terms and conditions, including any designed to limit the source's potential to emit, are enforceable by the Administrator and citizens under the Federal Act as well as the Commission.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.B.(1).)

1.23 Except as otherwise specified or limited herein, the open burning of residential, commercial, institutional, or industrial solid waste, is prohibited. This prohibition does not apply to infrequent burning of agricultural wastes in the field, silvi-cultural wastes for forest management purposes, land-clearing debris, debris from emergency clean-up operations, and ordnance. Open burning of land-clearing debris must not use starter or

auxiliary fuels which cause excessive smoke (rubber tires, plastics, etc.); must not be performed if prohibited by local ordinances; must not cause a traffic hazard; must not take place where there is a High Fire Danger Alert declared by the Mississippi Forestry Commission or an Emergency Air Pollution Episode Alert imposed by the Executive Director of the MDEQ and must meet the following buffer zones.

- (a) Open burning without a forced-draft air system must not occur within five hundred (500) yards of an occupied dwelling.
- (b) Open burning utilizing a forced-draft air system on all fires to improve the combustion rate and reduce smoke may be done within 500 yards of but not within fifty (50) yards of an occupied dwelling.
- (c) Burning must not occur within 500 yards of commercial airport property, private air fields, or marked off-runway aircraft approach corridors unless written approval to conduct burning is secured from the proper airport authority, owner or operator.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.G.)

1.24 Except as otherwise specified herein, the permittee shall be subject to the following provision with respect to emergencies:

- (a) Except as otherwise specified herein, an “emergency” means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include non-compliance to the extent caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.
- (b) An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions specified in Part (c) following are met.
- (c) The affirmative defense of emergency shall be demonstrated through properly signed contemporaneous operating logs, or other relevant evidence that include information as follows:
  - (1) An emergency occurred and that the permittee can identify the cause(s) of the emergency;
  - (2) The permitted facility was at the time being properly operated;
  - (3) During the period of the emergency the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other

requirements in the permit; and

- (4) The permittee submitted notice of the emergency to the MDEQ within two (2) working days of the time when emission limitations were exceeded due to the emergency. This notice must contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.
- (d) In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (e) This provision is in addition to any emergency or upset provision contained in any applicable requirement specified elsewhere herein.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.G.)

1.25 Except as otherwise specified herein, the permittee shall be subject to the following provisions with respect to upsets, start-ups, and shutdowns.

- (a) Upsets (as defined in 11 Miss. Admin. Code Pt. 2, R. 1.2.)
  - (1) For an upset, the Commission may pursue an enforcement action for noncompliance with an emission standard or other requirement of an applicable rule, regulation, or permit. In determining whether to pursue enforcement action, and/or the appropriate enforcement action to take, the Commission may consider whether the source has demonstrated through properly signed contemporaneous operating logs or other relevant evidence the following:
    - (i) An upset occurred and that the source can identify the cause(s) of the upset;
    - (ii) The source was at the time being properly operated;
    - (iii) During the upset the source took all reasonable steps to minimize levels of emissions that exceeded the emission standard or other requirement of an applicable rule, regulation, or permit;
    - (iv) That within five (5) working days of the time the upset began, the source submitted a written report to the Department describing the upset, the steps taken to mitigate excess emissions or any other non-compliance, and the corrective actions taken and;
    - (v) That as soon as practicable but no later than twenty-four (24) hours of becoming aware of an upset that caused an immediate adverse impact to human health or the environment beyond the source boundary or caused a general nuisance to the public, the source provided notification

to the Department.

- (2) In any enforcement proceeding by the Commission, the source seeking to establish the occurrence of an upset has the burden of proof.
  - (3) This provision is in addition to any upset provision contained in any applicable requirement.
  - (4) These upset provisions apply only to enforcement actions by the Commission and are not intended to prohibit EPA or third party enforcement actions.
- (b) Start-ups and Shutdowns (as defined in 11 Miss. Admin. Code Pt. 2, R. 1.2.)
- (1) Start-ups and shutdowns are part of normal source operation. Emission limitations apply during start-ups and shutdowns unless source specific emission limitations or work practice standards for start-ups and shutdowns are defined by an applicable rule, regulation, or permit.
  - (2) Where the source is unable to comply with existing emission limitations established under the State Implementation Plan (SIP) and defined in this Mississippi Administrative Code, Title 11, Part 2, Chapter 1, the Department will consider establishing source specific emission limitations or work practice standards for start-ups and shutdowns. Source specific emission limitations or work practice standards established for start-ups and shutdowns are subject to the requirements prescribed in Mississippi Administrative Code, Title 11, Part 2, Chapter 1, Rule 1.10.B.(2)(a) through (e).
  - (3) Where an upset as defined in Rule 1.2 occurs during start-up or shutdown, see the upset requirements above.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.10.)

- 1.26 The permittee shall comply with all applicable standards for demolition and renovation activities pursuant to the requirements of 40 CFR Part 61, Subpart M, as adopted by reference in Mississippi Administrative Code, Title 11, Part 2, Chapter 1, Rule 1.8. The permittee shall not be required to obtain a modification of this permit in order to perform the referenced activities.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.8.)

- 1.27 Regarding compliance testing (if applicable):

- (a) The results of any emissions sampling and analysis shall be expressed both in units consistent with the standards set forth in any Applicable Rules and Regulations or this permit and in units of mass per time.

- (b) Compliance testing will be performed at the expense of the permittee.
- (c) Each emission sampling and analysis report shall include (but not be limited to) the following:
  - (1) Detailed description of testing procedures;
  - (2) Sample calculation(s);
  - (3) Results; and
  - (4) Comparison of results to all Applicable Rules and Regulations and to emission limitations in the permit.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.6.B.(3), (4), and (6).)

## SECTION 2. EMISSION POINTS & POLLUTION CONTROL DEVICES

Emission Point	Description
AA-000	Facility-Wide (Stella-Jones Corporation – Durant)
AA-001	Pole Peeler
AA-002	Pole Drying Kiln [equipped with a 17.0 MMBTU / hour natural gas burner]
AA-003	Firebox Air Curtain Incinerator [used to dispose of clean lumber waste, wood waste, and yard waste generated on-site; max. throughput: 13 tons / hour; equipped with a 74 HP (55 kW) diesel-fired engine (manufactured in 2023)]
AA-004	Ash Management Operations
AA-005	Unpaved Roads [ <i>fugitive emissions</i> ]
AA-006	Wood Hog

## SECTION 3. EMISSION LIMITATIONS & STANDARDS

### A. FACILITY-WIDE EMISSION LIMITATIONS & STANDARDS

3.A.1 Except as otherwise specified or limited herein, the permittee shall not cause or allow the emission of smoke from a point source into the open air from any manufacturing, industrial, commercial or waste disposal process that exceeds forty percent (40%) opacity subject to the exceptions provided below:

- (a) Start-up operations may produce emissions, which exceed 40% opacity for up to fifteen (15) minutes per start-up in any one (1) hour and not to exceed three (3) start-ups per stack in any twenty-four (24) hour period.
- (b) Emissions resulting from soot blowing operations (i.e. ash removal) shall be permitted provided such emissions do not exceed sixty percent (60%) opacity and provided further that the aggregate duration of such emissions during any twenty-four (24) hour period does not exceed ten (10) minutes per billion BTU gross heating value of fuel in any one (1) hour.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.A)

3.A.2 Except as otherwise specified or limited herein, the permittee shall not cause or allow the discharge into the ambient air from any point source any air contaminant of such opacity as to obscure an observer's view to a degree in excess of 40% opacity equivalent to that provided in Condition 3.A.1. This shall not apply to vision obscuration caused by uncombined water droplets.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.B.)

3.A.3 The permittee shall not cause or allow the emission of particles or any contaminants in sufficient amounts or of such duration from any process as to be injurious to humans, animals, plants, or property, or to be a public nuisance, or create a condition of air pollution.

- (a) The permittee shall not cause or permit the handling, transporting, or storage of any material in a manner which allows or may allow unnecessary amounts of particulate matter to become airborne.
- (b) When dust, fumes, gases, mist, odorous matter, vapors, or any combination thereof escape from a building or equipment in such a manner and amount as to cause a nuisance to property other than that from which it originated or to violate any other provision of 11 Miss. Admin. Code Pt. 2, Ch. 1, the Commission may order such corrected in a way that all air and gases or air and gas-borne material leaving the building or equipment are controlled or removed prior to discharge to the open air.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.C.)

**B. EMISSION POINT SPECIFIC EMISSION LIMITATIONS & STANDARDS**

<b>Emission Point(s)</b>	<b>Applicable Requirement</b>	<b>Condition Number</b>	<b>Pollutant / Parameter</b>	<b>Limit / Standard</b>
AA-000	11 Miss. Admin. Code Pt. 2, R. 1.3.B.	3.B.1	Opacity	≤ 40%
	11 Miss. Admin. Code Pt. 2, R. 1.3.F.(1).	3.B.2	PM	$E = 4.1 \cdot (p^{0.67})$
AA-002 AA-003	11 Miss. Admin. Code Pt. 2, R. 1.3.A.	3.B.3	Opacity (as smoke)	≤ 40%
AA-002	11 Miss. Admin. Code Pt. 2, R. 1.3.D.(1)(b).	3.B.4	PM (filterable)	$E = 0.8808 \cdot (I^{-0.1667})$
	11 Miss. Admin. Code Pt. 2, R. 2.2.B.(10)., as established in the Permit to Construct issued March 16, 2023	3.B.5	VOCs (as WPP1)	0.04 lb. / ft <sup>3</sup>
AA-003	11 Miss. Admin. Code Pt. 2, R. 1.3.G.(2)(b) and 2.2.B.(14)(a), (e).	3.B.6	Buffer Zone Criteria	Install / Operate the ACI at Least 150 Feet From Any Dwelling, Light Commercial Building, Residential Area, or Recreational Area
	11 Miss. Admin. Code, Pt. 2, R. 1.3.H.(1).	3.B.7	PM (filterable)	0.2 grains / dscf (Calculated to 12% CO <sub>2</sub> by Volume)
	40 CFR Part 60, Subpart CCCC – Standards of Performance for Commercial and Industrial Solid Waste Incineration Units 40 CFR 60.2010 and 60.2015(a)(1); Subpart CCCC	3.B.8	Opacity	General Applicability
	40 CFR 60.2245(b) and 60.2265; Subpart CCCC 11 Miss. Admin. Code, Pt. 2, R. 2.2.B.(10)., as established in the Permit to Construct issued March 16, 2023	3.B.9	Waste Disposal Restriction	Only Incinerate Vegetative Waste
	40 CFR 60.2250; Subpart CCCC	3.B.10	Opacity	≤ 35% During Start-Up Periods; and ≤ 10% During Operations
AA-003 (Diesel Engine)	40 CFR Part 63, Subpart ZZZZ – NESHAP for Stationary Reciprocating Internal Combustion Engines 40 CFR 63.6585(a), (c), 63.6590(a)(2)(iii) and (c)(1); Subpart ZZZZ	3.B.11	HAPs	General Applicability



Emission Point(s)	Applicable Requirement	Condition Number	Pollutant / Parameter	Limit / Standard
AA-003 (Diesel Engine)	40 CFR Part 60, Subpart III – Standards of Performance for Stationary Compression Ignition Combustion Engines  40 CFR 60.4200(a)(2)(i); Subpart III	3.B.12	NMHC + NO <sub>x</sub>  CO  PM  Opacity (Smoke)	General Applicability
	40 CFR 60.4201(a), 60.4204(b), and 60.4206; Subpart III  Table 1 – Tier 4 Standards; 40 CFR Part 1039.101	3.B.13	NMHC + NO <sub>x</sub>	4.7 g / kW-hr
			CO	5.0 g / kW-hr
			PM	0.03 g / kW-hr
	40 CFR 60.4207(b); Subpart III	3.B.14	Fuel Requirement	15 ppm Max. Sulfur Content; and 40 Min. Cetane Index or 35% Max. Aromatic Content (by Volume)
40 CFR 60.4201(a) and 60.4204(b); Subpart III  40 CFR 1039.105; Subpart B	3.B.15	Opacity (Smoke)	20% During Acceleration Mode; 15% During Lugging Mode; and 50% During Peaks in Acceleration or Lugging Mode	

3.B.1 For Emission Point AA-000 (Facility-Wide), except as otherwise specified herein, the permittee shall not cause or allow the discharge into the ambient air from any point source any air contaminant or emissions of such opacity as to obscure an observer's view to a degree in excess of forty (40) percent opacity. This shall not apply to vision obscuration caused by uncombined water droplets.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.B.)

3.B.2 For Emission Point AA-000 (Facility-Wide), except as otherwise specified herein (or as applicable), the permittee shall not cause or allow the emission of particulate matter (PM) in total quantities in any one (1) hour from any manufacturing process (which includes any associated stacks, vents, outlets, or combination thereof) to exceed the amount determined by the relationship:

$$E = 4.1 \cdot (p^{0.67})$$

Where “E” is the emission rate in pounds per hour and “p” is the process weight input rate in tons per hour. Conveyor discharge of coarse solid matter may be allowed if no nuisance is created beyond the property boundary where the discharge occurs.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.F.(1).)

3.B.3 For Emission Points AA-002 and AA-003, except as otherwise specified herein, the permittee shall not cause or allow the emission of smoke into the open air that exceeds 40% opacity subject to the following exceptions:

- (a) Start-up operations may produce emissions which exceed 40% opacity for up to fifteen (15) minutes per startup in any one hour and not to exceed three (3) start-ups per stack in any twenty-four (24) hour period.
- (b) Emissions resulting from soot blowing operations shall be permitted provided such emissions do not exceed sixty (60) percent opacity and provided further that the aggregate duration of such emissions during any twenty-four (24) hour period does not exceed ten (10) minutes per billion BTU gross heating value of fuel in any one (1) hour.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.A.)

3.B.4 For Emission Point AA-002, the maximum permissible emission of ash and/or particulate matter (PM – filterable) from any fossil fuel burning installation with a heat input rate equal to / greater than ten (10) MMBTU per hour but less than 10,000 MMBTU per hour shall not exceed an emission rate as determined by the following relationship:

$$E = 0.8808 \cdot (I^{0.1667})$$

Where “E” is the emission rate in pounds per MMBTU per hour heat input and “I” is the heat input in MMBTU per hour.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.D.(1)(b).)

3.B.5 For Emission Point AA-002, the permittee shall limit the emission of volatile organic compounds as determined by Wood Products Protocol 1 (VOCs as WPP1) from the kiln to no more than 0.04 pounds per cubic foot (ft<sup>3</sup>) of poles dried.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B.(10)., as established in the Permit to Construct issued March 16, 2023)

3.B.6 For Emission Point AA-003, the permittee shall install and operate the air curtain incinerator (ACI) at least one hundred fifty (150) feet from any dwelling or any light commercial area not owned by the permittee and at least 150 feet from the nearest residential or recreational area.

For the purpose of this permit, the following terms shall be defined as such:

- (a) “*Light Commercial Area*” – an area zoned for commercial use, or, in the absence of any local zoning ordinances, an area predominantly used for wholesale and retail trade in goods and services.
- (b) “*Recreational Area*” – any area that meets one of the following criteria:

- (1) a national, state, county, or city park; or
  - (2) an outdoor recreational area (such as a golf course or swimming pool) owned by a city, county, state, or other public agency.
- (c) “*Residential Area*” – any area that meets one of the following criteria:
- (1) a group of twenty (20) or more single-family dwelling units on contiguous property and having an average density of two (2) or more units per acre;
  - (2) a group of forty (40) or more single-family dwelling units on contiguous property and having an average density of one (1) or more units per acre; or
  - (3) a subdivision containing at least 20 constructed houses in which the subdivision plat is recorded in the chancery clerk's office of the appropriate county.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.G.(2)(b). and R. 2.2.B.(14)(a), (e).)

- 3.B.7 For Emission Point AA-003, the maximum discharge of particulate matter (PM) from the ACI shall not exceed 0.2 grains per dry standard cubic foot (dscf) calculated to twelve (12) percent carbon dioxide (CO<sub>2</sub>) by volume. This limitation shall apply when the ACI is operating at its designed capacity.

(Ref.: 11 Miss. Admin. Code, Pt. 2, R. 1.3.H.(1).)

- 3.B.8 For Emission Point AA-003, the permittee is subject to and shall comply with the applicable requirements found in 40 CFR Part 60, Subpart CCCC – Standards of Performance for Commercial and Industrial Solid Waste Incineration Units and 40 CFR Part 60, Subpart A – General Provisions.

(Ref.: 40 CFR 60.2010 and 60.2015(a)(1); Subpart CCCC)

- 3.B.9 For Emission Point AA-003, the permittee shall only incinerate vegetative waste. For the purpose of this permit, “vegetative waste” is considered a 100 percent mixture of wood waste, clean lumber waste, and/or yard waste. Moreover, the following terms shall be defined as such:

- (a) “*Wood waste*” is defined as untreated wood and untreated wood products – including tree stumps (whole or chipped), trees, tree limbs (whole or chipped), bark, sawdust, chips, scraps, slabs, millings, and shavings.
- (b) “*Clean lumber waste*” is defined as wood or wood products that have been cut or shaped and include wet, air-dried, and kiln-dried wood products (but does not wood products that have been painted, pigment-stained, or pressure-treated by compounds such as chromate copper arsenate, pentachlorophenol, and creosote).

- (c) “*Yard waste*” is defined as grass, grass clippings, bushes, shrubs, and clippings from bushes and shrubs as a result of maintaining yards.

(Ref.: 40 CFR 60.2245(b) and 60.2265; Subpart CCCC)

(Ref.: 11 Miss. Admin. Code, Pt. 2, R. 2.2.B.(10)., as established in the Permit to Construct issued March 16, 2023)

- 3.B.10 For Emission Point AA-003, the permittee shall comply with the following opacity limitations:

- (a) Maintain an opacity of less than or equal to thirty-five (35) percent during any start-up period in which “start-up” is considered the first thirty (30) minutes of operation; and
- (b) Except as provided in paragraph (a) of this condition and during periods of malfunction, maintain an opacity of less than or equal to ten (10) percent (10%) at all times.

(Ref.: 40 CFR 60.2250; Subpart CCCC)

- 3.B.11 For Emission Point AA-003 (Diesel Engine), the permittee is subject to and shall comply with the applicable requirements found in 40 CFR Part 63, Subpart ZZZZ – National Emissions Standards for Hazardous Air Pollutants (NESHAP) for Stationary Reciprocating Internal Combustion Engines (RICE) and 40 CFR Part 63, Subpart A – General Provisions (as required in Table 8 of Subpart ZZZZ).

For the purpose of this permit, stationary RICE is classified as “new” if construction or reconstruction commenced on / after December 19, 2002.

For new compression-ignition RICE, the permittee shall comply with the applicable requirements in Subpart ZZZZ by complying with 40 CFR Part 60, Subpart IIII – Standards of Performance for Stationary Compression Ignition (CI) Combustion Engines, except for the initial notification requirements of Condition 5.C.8. No further requirements apply for such engines under Subpart ZZZZ.

(Ref.: 40 CFR 63.6585(a), (c), 63.6590(a)(2)(iii), and (c)(1); Subpart ZZZZ)

- 3.B.12 For Emission Point AA-003 (Diesel Engine), the permittee is subject to and shall comply with all applicable requirements found in 40 CFR Part 60, Subpart IIII – Standards of Performance for Stationary Compression Ignition Internal Combustion Engines and 40 CFR Part 60, Subpart A – General Provisions (as required by Table 8 of Subpart IIII).

(Ref.: 40 CFR 60.4200(a)(2)(i); Subpart IIII)

- 3.B.13 For Emission Point AA-003 (Diesel Engine), the permittee shall comply with the following emissions standards:

- (a) Non-Methane Hydrocarbons and Nitrogen Oxides (NMHC + NO<sub>x</sub>): 4.7 grams per kilowatt-hour (g / kW-hr);
- (b) Carbon Monoxides (CO): 5.0 grams per kilowatt-hour; and
- (c) Particulate Matter (PM): 0.40 grams per kilowatt-hour.

The permittee shall operate and maintain each engine in such a manner to achieve the referenced emission standards over the entire life of the engine.

(Ref.: 40 CFR 60.4201(a), 60.4204(b), and 60.4206; Subpart IIII)

3.B.14 For Emission Points AA-003 (Diesel Engine), the permittee shall only combust diesel fuel within each engine that meet the following requirements (on a per-gallon basis):

- (a) A maximum sulfur content of fifteen (15) part per million (ppm); and
- (b) A minimum cetane index of forty (40) or a maximum aromatic content of thirty-five (35) volume percent.

(Ref.: CFR 60.4207(b); Subpart IIII)

3.B.15 For Emission Point AA-003 (Diesel Engine), the permittee shall not discharge into the atmosphere any smoke exhaust that exceeds the following opacity standards:

- (a) Twenty (20) percent during the acceleration mode;
- (b) Fifteen (15) percent during the lugging mode; and
- (c) Fifty (50) percent during the peaks in either the acceleration or lugging modes.

The permittee shall operate and maintain the engine in such a manner to achieve the referenced emission standards over the entire life of the engine.

(Ref.: 40 CFR 60.4201(a) and 60.4204(b); Subpart IIII)

(Ref.: 40 CFR 1039.105; Subpart B)

C. INSIGNIFICANT AND TRIVIAL ACTIVITY EMISSION LIMITATIONS & STANDARDS

Applicable Requirement	Condition Number	Pollutant / Parameter	Limit / Standard
11 Miss. Admin. Code Pt. 2, R. 1.3.D.(1)(a).	3.C.1	PM	0.6 lb. / MMBTU
11 Miss. Admin. Code Pt. 2, R. 1.4.A.(1).	3.C.2	SO <sub>2</sub>	4.8 lb. / MMBTU

3.C.1 The maximum permissible emission of ash and/or particulate matter (PM) from any fossil fuel burning installation of less than ten (10) MMBTU per hour heat input shall not exceed 0.6 pounds per MMBTU per hour heat input.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.D.(1)(a).)

3.C.2 The maximum discharge of sulfur oxides from any fuel burning installation in which the fuel is burned primarily to produce heat or power by indirect heat transfer shall not exceed 4.8 pounds (measured as sulfur dioxide) per MMBTU heat input.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.4.A.(1).)

D. WORK PRACTICE STANDARDS

Emission Point(s)	Applicable Requirement	Condition Number	Pollutant / Parameter	Limit / Standard
AA-003	11 Miss. Admin. Code Pt. 2, R. 2.2.B.(10)., as established in the Permit to Construct issued March 16, 2023	3.D.1	PM	Operate and Maintain the ACI in Accordance with the Manufacturer's Written Instructions
		3.D.2		Operational Criteria Requirements
		3.D.3	Fuel Restriction	Fuel Restriction Requirements
AA-003 (Diesel Engine)	40 CFR 60.4211(a); Subpart III	3.D.4	NMHC + NO <sub>x</sub> CO PM Opacity (Smoke)	Perform Compliance Practices
AA-004	11 Miss. Admin. Code Pt. 2, R. 2.2.B.(10)., as established in the Permit to Construct issued March 16, 2023	3.D.5	PM	Ash Management Requirements

3.D.1 For Emission Point AA-003, the permittee shall operate and maintain the ACI according to the manufacturer's written instructions to ensure complete combustion of the material charged into the firebox. Additionally, the permittee shall maintain the manufacturer's recommendations on-site.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B.(10)., as established in the Permit to Construct issued March 16, 2023)

3.D.2 For Emission Point AA-003, the permittee shall not store or locate combustible material within 100 feet of the ACI in any direction. Additionally, the permittee shall operate the ACI in accordance with any setbacks recommended by the manufacturer for specified wind speeds.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B.(10)., as established in the Permit to Construct issued March 16, 2023)

3.D.3 For Emission Point AA-003, the permittee shall only utilize gasoline, kerosene, diesel fuel, or No. 2 fuel oil as the fuel source for any start-up fire within the ACI. Additionally, the permittee shall minimize (to the best extent practicable) the amount of fuel necessary to ignite a start-up fire.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B.(10)., as established in the Permit to Construct issued March 16, 2023)

3.D.4 For Emission Point AA-003 (Diesel Engine), the permittee shall demonstrate compliance with the emission standards outlined in Conditions 3.B.14 by performing the following work practices:

- (a) Operate and maintain each engine and control device (if any) according to the manufacturer's emission-related written instructions;
- (b) Change only those emission-related settings that are permitted by the manufacturer; and
- (c) Meet the requirements of 40 CFR Part 1068 (as applicable).

(Ref.: 40 CFR 60.4211(a); Subpart III)

3.D.5 For Emission Point AA-004, the permittee shall comply with the following work practices to minimize ash becoming airborne during removal, transfer, and/or storage activities:

- (a) The permittee shall remove any accumulated ash within the ACI at the frequency specified in the manufacturer's written instructions;
- (b) After sufficient time for cooling (and as necessary), the permittee shall wet ash within the ACI prior to its removal; and
- (c) The permittee shall store cooled ash in a roll-off container, trailer, or other equivalent container. Additionally, the permittee shall wet and/or cover stored ash as necessary.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.2.B.(10), as established in the Permit to Construct issued March 16, 2023)



## **SECTION 4. COMPLIANCE SCHEDULE**

- 4.1 Unless otherwise specified herein, the permittee shall be in compliance with all requirements contained herein upon issuance of this permit.
- 4.2 Except as otherwise specified herein, the permittee shall submit to the Permit Board and to the Administrator of EPA Region IV a certification of compliance with permit terms and conditions (including emission limitations, standards, or work practices) by January 31 of each year for the preceding calendar year. If the permit was reissued or modified during the course of the preceding calendar year, the compliance certification shall address each version of the permit. Each compliance certification shall include the following items:
- (a) The identification of each term or condition of the permit that is the basis of the certification;
  - (b) The compliance status;
  - (c) Whether compliance was continuous or intermittent;
  - (d) The method(s) used for determining the compliance status of the source, currently and over the applicable reporting period;
  - (e) Such other facts as may be specified as pertinent in specific conditions elsewhere in this permit.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.C.(5)(a), (c), and (d).)

## **SECTION 5. MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS**

### **A. GENERAL MONITORING, RECORDKEEPING AND REPORTING REQUIREMENTS**

5.A.1 The permittee shall install, maintain, and operate equipment and/or institute procedures as necessary to perform the monitoring and recordkeeping specified below.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3).)

5.A.2 In addition to the recordkeeping specified below, the permittee shall include with all records of required monitoring information the following:

- (a) The date, place as defined in the permit, and time of sampling or measurements;
- (b) The date(s) analyses were performed;
- (c) The company or entity that performed the analyses;
- (d) The analytical techniques or methods used;
- (e) The results of such analyses; and
- (f) The operating conditions existing at the time of sampling or measurement.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(b)(1).)

5.A.3 Except where a longer duration is specified in an applicable requirement, the permittee shall retain records of all required monitoring data and support information for a period of at least five (5) years from the date of the monitoring sample, measurement, report, or application. Supporting information includes all calibration and maintenance records, all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by the permit.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(b)(2).)

5.A.4 Except as otherwise specified herein, the permittee shall submit reports of any required monitoring by July 31 and January 31 of each calendar year for the preceding six-month period. All instances of deviations from permit requirements must be clearly identified in such reports and all required reports must be certified by a responsible official consistent with Mississippi Administrative Code, Title 11, Part 2, Chapter 6, Rule 6.2.E.

For applicable periodic reporting requirements in 40 CFR Parts 60, 61, and 63, the permittee shall comply with the deadlines in this condition for reporting conducted on a semiannual basis. Additionally, any required quarterly reports shall be submitted by the end of the month following each calendar quarter (i.e. April 30, July 31, October 31, and January 31) and any required annual reports shall be submitted by January 31 following each calendar year.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(c)(1).)

(Ref.: 40 CFR 60.19(c), 61.10(g), and 63.10(a)(5); Subpart A)

- 5.A.5 Except as otherwise specified herein, the permittee shall report all deviations from permit requirements, including those attributable to upsets, the probable cause of such deviations, and any corrective actions or preventive measures taken. The report shall be made within five (5) working days of the time the deviation began.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(c)(2).)

- 5.A.6 Except as otherwise specified herein, the permittee shall perform emissions sampling and analysis in accordance with EPA Test Methods and with any continuous emission monitoring requirements, if applicable. All test methods shall be those versions or their equivalents approved by the MDEQ and the EPA.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3).)

- 5.A.7 The permittee shall maintain records of any alterations, additions, or changes in equipment or operation.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3).)

- 5.A.8 Unless otherwise specified in Section 4, upon permit issuance, the monitoring, testing, recordkeeping, and reporting requirements of Section 5 herein supersede the requirements of any preceding permit to construct and/or operate.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3).)

**B. SPECIFIC MONITORING AND RECORDKEEPING REQUIREMENTS**

<b>Emission Point(s)</b>	<b>Applicable Requirement</b>	<b>Condition Number</b>	<b>Pollutant / Parameter Monitored</b>	<b>Monitoring / Recordkeeping Requirement</b>
AA-002	11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(a)(2).	5.B.1	Dried Lumber Throughput	Monitor Total Throughput (Monthly and Rolling 12-Month Total)
		5.B.2	Final Moisture Content	Continuously Monitor the Moisture Content of All Lumber Dried Calculate the Overall Average Moisture Content Monthly
AA-003	11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(a)(2).	5.B.3	PM Opacity	Conduct an Annual Inspection
	40 CFR 60.2255; Subpart CCCC 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(a)(2).	5.B.4	Opacity	Conduct Routine Method 9 Testing
	40 CFR 60.2260(b) and (f); Subpart CCCC 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(a)(2).	5.B.5	Hours of Operation Opacity	Maintain Documentation on Required Information
AA-003 (Diesel Engine)	40 CFR 60.4211(g)(3); Subpart III	5.B.6	NMHC + NO <sub>x</sub>	Perform Compliance Demonstration (As Applicable)
	40 CFR 60.4214(a)(2); Subpart III	5.B.7	CO PM	Recordkeeping Requirements

5.B.1 For Emission Point AA-002, the permittee shall monitor and maintain the total throughput of poles dried within the kiln in cubic feet (ft<sup>3</sup>) on both a monthly and rolling 12-month basis.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(a)(2).)

5.B.2 For Emission Point AA-002, the permittee shall monitor and maintain the average moisture content of each kiln charge on a monthly basis. The permittee shall utilize this moisture content data to calculate and maintain the overall average moisture content for each monthly period.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(a)(2).)

5.B.3 For Emission Point AA-003, the permittee shall perform an inspection of the ACI in accordance with the manufacturer's recommendations no later than twelve (12) months after the initial start-up. Thereafter, the permittee shall perform subsequent inspections on an annual basis (at a minimum) not to exceed twelve (12) months after the previously

completed inspection. If any problem is noted during an inspection, the permittee shall perform the necessary maintenance activities to ensure operation of the ACI as original designed.

The permittee shall maintain documentation that details the date / time of each inspection the results of each inspection, any problem denoted during an inspection, and any maintenance (either corrective or preventative) performed to the ACI.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(a)(2).)

5.B.4 For Emission Point AA-003, the permittee shall demonstrate compliance with the opacity limits specified in Condition 3.B.11 by conducting routine opacity testing on the exhaust emitted from the ACI in accordance with EPA Test Method 9 (i.e. "Method 9") and the following requirements:

- (a) The initial testing shall be conducted no later than sixty (60) days after the ACI reaches the maximum charge rate at which it will operate but no later than one hundred eighty (180) days after initial start-up. Thereafter, the permittee shall conduct subsequent testing on an annual basis not to exceed twelve (12) months after the previously completed evaluation.
- (b) Each test (or part of a test) shall be performed during daylight hours and during representative operating conditions.
- (c) Unless otherwise specified herein, the result of each test shall be determined from the average of three (3) 1-hour blocks. Each block shall consist of the average from ten (10) 6-minute evaluations, and each 6-minute evaluation shall be the average of twenty-four (24) total consecutive observations completed once every fifteen (15) seconds.
- (d) For the initial testing to demonstrate compliance with Condition 3.B.11(a), the permittee shall evaluate six (6) separate start-up periods in order to satisfy the criteria outlined in paragraph (c) of this condition.

For any subsequent testing, the permittee may demonstrate compliance with the noted opacity limit by evaluating (at a minimum) one (1) start-up period.

- (e) For the initial testing to demonstrate compliance with Condition 3.B.11(b), the permittee shall evaluate an operational period (or number of operational periods, except for periods of malfunction or start-up) that satisfies the criteria outlined in paragraph (c) of this condition.

For any subsequent testing, the permittee shall evaluate an operational period (or number of operational periods, except for periods of malfunction or start-up) within the applicable 12-month span that satisfies the criteria outlined in paragraph (c) to the best extent practicable. If the total operational period does not satisfy the criteria outlined in paragraph (c), the permittee shall determine a result from the

completed testing and maintain documentation that details the duration of the non-evaluated period (and why the permittee was unable to evaluate the noted period).

(Ref.: 40 CFR 60.2255; Subpart CCCC)

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(a)(2).)

5.B.5 For Emission Point AA-003, the permittee shall maintain documentation that contain the following information:

- (a) The hours of operation in which the authorized wastes (as specified in Condition 3.B.10) are incinerated on a monthly basis;
- (b) The results from the initial and annual opacity tests completed for at least five (5) years; and
- (c) A copy of the initial and annual opacity reports for period of at least five (5) years.

(Ref.: 40 CFR 60.2260(b) and (f); Subpart CCCC)

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(a)(2).)

5.B.6 For Emission Point AA-003 (Diesel Engine), the permittee shall demonstrate compliance through with the emission standards specified in Condition 3.B.14 through the following actions if the permittee does not operate and maintain the engine according to the manufacturer's emission-related written instructions or the permittee changes emission-related settings in a way that is not permitted by the manufacturer:

- (a) Keep a maintenance plan, records of conducted maintenance, and (to the extent practicable) maintain and operate the engine in a manner consistent with good air pollution control practice for minimizing emissions; and
- (b) Conduct an initial performance test to demonstrate compliance with the applicable emission standards within one (1) year after the permittee changes emission-related settings in a way that is not permitted by the manufacturer.

(Ref.: 40 CFR 60.4211(g)(1); Subpart IIII)

5.B.7 For Emission Points AA-003 (Diesel Engine), the permittee shall maintain documentation that details the following information:

- (a) All notifications submitted to comply with Subpart IIII;
- (b) Any maintenance conducted on an engine; and
- (c) Documentation from the manufacturer that indicate an engine is certified to meet the emission standards specified in Conditions 3.B.14, 3.B.15, and 3.B.16.

(Ref.: 40 CFR 60.4214(a)(2); Subpart IIII)

C. SPECIFIC REPORTING REQUIREMENTS

Emission Point(s)	Applicable Requirement	Condition Number	Pollutant / Parameter Monitored	Reporting Requirement
AA-002 AA-003	11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(c)(1).	5.C.1	Total Throughput Final Moisture Content Hours of Operation (ACI)	Submit a Semi-Annual Monitoring Report
AA-003	40 CFR 60.2260(a); Subpart CCCC	5.C.2	Opacity	Submit a Notification on the Planned Date for ACI Installation and Start-Up
	40 CFR 60.2260(d); Subpart CCCC	5.C.3	Opacity	Submit the Method 9 Test Results

5.C.1 For Emission Point AA-002 and AA-003, the permittee shall submit a semi-annual monitoring report (SMR) in accordance with Condition 5.A.4 that contains the following information:

- (a) The total throughput of poles dried within the kiln in cubic feet (ft<sup>3</sup>) on both a monthly and rolling 12-month basis;
- (b) The average final moisture content of all poles dried within the kiln on a monthly basis; and
- (c) The total hours of operation in which authorized vegetative wastes are incinerated on a monthly basis.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A.(3)(c)(1).)

5.C.2 For Emission Point AA-003, the permittee shall submit a notification to the MDEQ that details the planned date for the installation and start-up of the ACI at least ten (10) days prior to the actual event(s).

(Ref.: 40 CFR 60.2260(a); Subpart CCCC)

5.C.3 For Emission Point AA-003, the permittee shall submit the results of the initial opacity test required by Condition 5.B.4 no later than sixty (60) days after completing the test in full. Thereafter, the permittee shall submit the results (and any supporting documentation – as applicable) of all subsequent testing no later than twelve (12) months after the previously submitted results.

(Ref.: 40 CFR 60.2260(d); Subpart CCCC)

**SECTION 6. ALTERNATIVE OPERATING SCENARIOS**

6.1 None permitted.



## SECTION 7. TITLE VI REQUIREMENTS

The following are applicable or potentially applicable requirements originating from Title VI of the Clean Air Act – Stratospheric Ozone Protection. The full text of the referenced regulations may be found on-line at <http://www.ecfr.gov/> under Title 40, or MDEQ shall provide a copy upon request from the permittee.

- 7.1 If the permittee produces, transforms, destroys, imports or exports a controlled substance or imports or exports a controlled product, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart A – Production and Consumption Controls.
- 7.2 If the permittee performs service on a motor vehicle for consideration when this service involves the refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart B – Servicing of Motor Vehicle Air Conditioners.
- 7.3 The permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart E – The Labeling of Products Using Ozone-Depleting Substances, for the following containers and products:
  - (a) All containers in which a class I or class II substance is stored or transported;
  - (b) All products containing a class I substance; and
  - (c) All products directly manufactured with a process that uses a class I substance, unless otherwise exempted by this subpart or, unless EPA determines for a particular product that there are no substitute products or manufacturing processes for such product that do not rely on the use of a class I substance, that reduce overall risk to human health and the environment, and that are currently or potentially available. If the EPA makes such a determination for a particular product, then the requirements of this subpart are effective for such product no later than January 1, 2015.
- 7.4 If the permittee performs any of the following activities, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart F – Recycling and Emissions Reduction:
  - (a) Servicing, maintaining, or repairing appliances;
  - (b) Disposing of appliances, including small appliances and motor vehicle air conditioners; or
  - (c) Refrigerant reclaimers, technician certifying programs, appliance owners and operators, manufacturers of appliances, manufacturers of recycling and recovery equipment, approved recycling and recovery equipment testing organizations, as well as persons selling, offering for sale, and/or purchasing class I, class II, or non-exempt substitute refrigerants.

- 7.5 The permittee shall be allowed to switch from any ozone-depleting substance to any acceptable alternative that is listed in the Significant New Alternatives Policy (SNAP) program promulgated pursuant to 40 CFR Part 82, Subpart G – Significant New Alternatives Policy Program. The permittee shall also comply with any use conditions for the acceptable alternative substance.
- 7.6 If the permittee performs any of the following activities, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart H – Halon Emissions Reduction:
- (a) Any person testing, servicing, maintaining, repairing, or disposing of equipment that contains halons or using such equipment during technician training;
  - (b) Any person disposing of halons;
  - (c) Manufacturers of halon blends; or
  - (d) Organizations that employ technicians who service halon-containing equipment.

## APPENDIX A

### List of Abbreviations Used In this Permit

BACT	Best Available Control Technology
CEM	Continuous Emission Monitor
CEMS	Continuous Emission Monitoring System
CFR	Code of Federal Regulations
CO	Carbon Monoxide
COM	Continuous Opacity Monitor
COMS	Continuous Opacity Monitoring System
DEQ	Mississippi Department of Environmental Quality
EPA	United States Environmental Protection Agency
gr/dscf	Grains Per Dry Standard Cubic Foot
HP	Horsepower
HAP	Hazardous Air Pollutant
lb/hr	Pounds per Hour
M or K	Thousand
MACT	Maximum Achievable Control Technology
MM	Million
MMBTUH	Million British Thermal Units per Hour
NA	Not Applicable
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emissions Standards for Hazardous Air Pollutants, 40 CFR Part 61, or National Emission Standards for Hazardous Air Pollutants for Source Categories, 40 CFR Part 63
NM VOC	Non-Methane Volatile Organic Compounds
NO <sub>x</sub>	Nitrogen Oxides
NSPS	New Source Performance Standards, 40 CFR 60
O&M	Operation and Maintenance
PM	Particulate Matter
PM <sub>10</sub>	Particulate Matter less than 10 µm in diameter
PM <sub>2.5</sub>	Particulate Matter less than 2.5 µm in diameter
ppm	Parts per Million
PSD	Prevention of Significant Deterioration
SIP	State Implementation Plan
SO <sub>2</sub>	Sulfur Dioxide
SSM	Startup, Shutdown, and Malfunction
TPY	Tons per Year
TRS	Total Reduced Sulfur
VEE	Visible Emissions Evaluation
VHAP	Volatile Hazardous Air Pollutant
VOHAP	Volatile Organic Hazardous Air Pollutant
VOC	Volatile Organic Compound