REV

MISSISSIPPI ASBESTOS DEMOLITION/RENOVATION NOTIFICATION FORM

Mail notification to: MDEQ Asbestos and Lead Branch, 515 E. Amite Street, Jackson, MS 39201

	EQ Asbestos and Lead Branc	Data Passived	oti cet, ou	I Al Number	
MDEQ Use Only: ★Email □Mail □Hand Delivery	Postmark (mail only)	Date Received 12/20/2024 AI Number 9342		9342	
I. Type of Notification (O=Original R=Revised	C=Canceled A= Annual): R				
II TYPE OF OPERATION (D=Demo O= Orde	red Demo R=Renovation E=Emer.	Renovation): R			
III. FACILITY DESCRIPTION (Include building	name, number and floor or room no	_{umber):} ERT Bu	ilding		
Bldg. Name: N/A					
Address: 157 Buck Creek Rd					
City: New Augusta	State: MS		Zip: 39462		
Site Location: New Augusta, MS			Tel: 601-964-8411		
Building Size: N/A	# of Floors: N/A			Ά	
Present Use: N/A	Prior Use: N/A				
IV. FACILITY INFORMATION (Identify owner	, asbestos removal contractor, and	other operator)			
OWNER NAME: Leaf River Cellulo					
Address: 157 Buck Creek Rd					
City: New Augusta	State: MS		39462		
Contact: Chris Carroll		Tel:	601-606-	3601	
ASBESTOS REMOVAL CONTRACTOR: Ibe	erville Companies LLC				
Address: 11637 Sunbelt Court					
_{City:} Baton Rouge	State: LA		_{Zip:} 70809		
Contact: Joseph Lambert			Tel: 225-252-1764		
Certification Number: ABC-00009701		Expiration Date	Expiration Date: 11/8/2025		
OTHER OPERATOR: N/A					
Address: N/A					
City: N/A			Zip:		
Contact:		Tel			
V. WAS SITE INSPECTED TO DETERMINE	PRESENCE OF ASBESTOS? (Ye	es/No): Yes			
WAS ASBESTOS PRESENT? (Yes/No): Yes Inspect			tion Date: 11/4/2022		
I SS IZ adad	I OAKOOWANOOWANAWAY ABI-I	00011180	Expirat	ion Date: 11/22/2023	
VI. SUSPECT MATERIALS SAMPLED AND	PROCEDURES USED TO DETEC	CT THE PRESENC	eulte eulte	STOS HIAT LIMAL	
CA labs used Polarized light N	Aicroscopy- See allache	ed lesting ive	suito,		
	-D.				
VII. QUANTITY OF RACM TO BE REMOVE	^{ED:} N/A			756	
Pipes (LN FT): N/A	Surface Area (SQ FT): 1521	Volu	me of Facilit	y Components (CU FT); 756	
VIII. QUANTITY OF NONFRIABLE ASBES	TOS NOT REMOVED:				
Category I: Yes		Category II: No		2.44.2025	
IX SCHEDULED DATES ASBESTOS REN	IOVAL (MM/DD/YY) Start: 1-13-	2025	Comp	lete: 3-14-2025	
X. SCHEDULED DATES DEMO/RENOVAT	TION (MM/DD/YY) Start: 1-13-20	025	Comp	_{lete:} 3-14-2025	

XI. DESCRIPTION OF PLANNED DEMOLITION OR RENOVA	TION WORK, AND ME	ETHOD(S)	TO BE USED:
Wet Method			
XII. DESCRIPTION OF WORK PRACTICES AND ENGINEERIN DEMOLITION OR RENOVATION SITE:	NG CONTROLS TO B	E USED TO	O PREVENT EMISSIONS OF ASBESTOS AT THE
Wet Method.			
XIII. WASTE TRANSPORTER #1 Republic Services			
Name: Republic Services			
Address: 1035 Old Brandon Rd			
City: Flowood	State: MS		Zip: 39232
Contact Person: Jonathan Johnson		Т	Tel: 601-420-8271
WASTE TRANSPORTER #2 N/A			
Name:			
Address:			
City:	State:	2	Zip:
Contact Person:			Tel:
XIV. WASTE DISPOSAL SITE Pine Belt Regional Solid	l Waste Manager	ment Aut	thority
Name: Pine Belt Regional Solid Waste Manageme	ent Authority		
Address: 5279 MS-29			
City: Ovett	State: MS		Zip: 39464
Contact Person: Tony Harris		1	_{Tel:} 601-515-2121
XV. IF DEMOLITION ORDERED BY A GOVERNMENT AGEN	CY, PLEASE IDENTI	FY THE AG	ENCY BELOW:
Name:		Title:	
Authority:			
Date of Order (MM/DD/YY):	Date C	Ordered to E	Begin (MM/DD/YY):
XVI. FOR EMERGENCY RENOVATIONS: N/A			
Date and Hour of Emergency (MM/DD/YY):			
Description of the sudden unexpected event:			я.
Explanation of how the event caused unsafe conditions or wou	ld cause equipment da	amage or a	ın unreasonable financial burden:
XVII. DESCRIPTION OF PROCEDURES TO BE FOLLOWED NONFRIABLE ASTESTOS MATERIAL BECOMES CRUMBL	.ED, PULVERIZED, O	N KEDOOL	LD TO TOUBLE
Stop work and notify a supervisor. Consul	t with Joseph L	_ambert	t on the proper next steps.
XVIII. I CERTIFY THAT AN INDIVIDUAL TRAINED IN THE P	ROVISIONS OF THIS	REGULAT	TION (40 CFR PART 61, SUBPART M) WILL BE
XVIII. I CERTIFY THAT AN INDIVIDUAL TRAINED IN THE P ONSITE DURING THE DEMOLITION OR RENOVATION, AN THIS PERSON WILL BE AVAILABLE FOR INSPECTION DU			
Joel M Engle Type or Print Name	Signature of Owner/C	Operator)	(Date)
XIX. I CERTIFY THAT THE ABOVE INFORMATION IS CORE	Just 19	3	12.20-24
Type or Print Name	(Signature of Owner/C	'Operator)	(Date)

CBR 33118603

Laboratory: Address: City, State, Zip BATON TOUGE, LA Analytical Accessor Lead PLM TEM Chips PCM AIR Whipes	Condition of Material Verbal Results		Courrier Sample Receipt Temp *F Seal Intact Y / N Sample Tags Y / N
Project 70-14/2 Facility: GP LEAF RIVER New Ausus 774, MS Contractor: Industrial Asbestos Removal Date: 11/4/22	Signature: Merendez		Racaived by (Signature) Received by (Signature) Time Time Time Time The Market Signature)
ASBESTOS REMOVAL RSBESTOS REMOVAL 11637 Subelt Court Baton Rouge, La 70809 Tel: (225) 620-0640 Cell: (225) 252-1764	3	1 NoKTH SIDE 3 SOUTH SIDE 4 WEST SIDE	Remarks Reinduished by (Signature) Remarks Reinduished by (Signature) Remarks

Dedicated to Quality

CA Labs, L.L.C.

12232 Industriplex, Suite 32 Baton Rouge, LA 70809 Phone 225-751-5632 Fax 225-751-5634



NVLAP #200772-0 TDSHS #300370 **CDPHE #AL-18111** LELAP #03069

Materials Characterization - Bulk Asbestos Analysis

Laboratory Analysis Report - Polarized Light

Industrial Asbestos Removal, LLC

11637 Sunbelt Court Baton Rouge, LA 70809 Attn: Joseph Lambert

Customer Project: GP Leaf River New Augusta, MS Date:

CBR22118602 Reference #:

11/8/2022

Analysis and Method

Summary of polarizing light microscopy (PLM / Stereomicroscopy bulk asbestos analysis) using the methods described in 40CFR Part 763 Appendix E to Subpart E (Interim and EPA 600 / R-93 / 116 (Improved). The sample is first viewed with the aid of stereomicroscopy. Numerous liquid slide preparations are created for analysis under the polarized microscope where identifications and quantifications are preformed. Calibrated liquid refractive oils are used as liquid mouting medium. These oils are used for identification (dispersion staining). A calibrated visual estimation is reported, should any asbestiform mineral be present. Other techniques such as acid washing are used in conjugation with refractive oils for detection of smaller quantities of asbestos. All asbestos percentages are based on calibrated visual estimation traceable to NIST standards for regulated of asbestos. Traceability to measurement and calibration is achieved by using known amounts and types of asbestos from standards where analyst and laboratory accuracy are measured. As little as 0.001% asbestos can be detected in favorable samples, while detection in unfavorable samples may approach the detection limit of 0.50% (well above the laboratory definition of trace).

Discussion

Vermiculite containing samples may have trace amounts of actinolite-tremolite, where not found be PLM should be analyzed using TEM methods and / or water separation techniques. Suspected actinolite/vermiculite presence will be indicated through the sample comment section of this report.

Fibrous talc containing samples may even contain a related asbestos fiber known as anthophyllite. Under certain conditions the same fiber may actually contain both talc and anthophyllite (a phenomenon called intergrowth). Again, TEM detection methods are recommended. CA Labs PLM report comments will denote suspected amounts of asbestiform anthophyllite with talc, where further analysis is recommended.

Some samples (floor tiles, surfacings, etc.) may contain fibers too small to be detectable by PLM analysis and should be analyzed by TEM bulk protocols.

A "trace asbestos" will be reported if the analyst observes far less than 1% asbestos. CA Labs defines "trace asbestos" as a few fibers detected by the analyst in several preparations and will indicate as such under these circumstances.

Quantification of <1% will actually be reported as <=1% (allowable variance close to 1% is high). Such results are ideal for point counting, and the technique is mandatory for friable samples (NESHAP, Nov. 1990 and clarification letter 8 May 1991) under 1% percent asbestos and the "trace asbestos". In order to make all initial PLM reports issued from CA Labs NESHAP compliant, all <1% asbestos results (except floor tiles) will be point counted at no additional charge.

Qualifications

CA Labs is accredited by the National Voluntary Accreditation Program (NVLAP) for selected test methods for airborne fiber analysis (TEM), and for bulk asbestos fiber analysis (PLM). All analysts have a college degree in a natural science (geology, biology, or environmental science) or are recognized by a state professional board in one these disciplines .Extensive in-house training programs are used to augment education background of the analyst. The group leader of polarized light has received supplemental McCrone Research training for asbestos identification. This report is not covered by the scope of AlHA accreditation. Analysis performed at CA Labs, LLC 12232 Industriplex, Suite 32 Baton Rouge, LA 70809.

Dedicated to Quality

CA Labs, L.L.C.

12232 Industriplex, Suite 32 Baton Rouge, LA 70809 Phone 225-751-5632 Fax 225-751-5634



NVLAP #200772-0 TDSHS #300370 **CDPHE #AL-18111** LELAP #03069

Overview of Project Sample Material Containing Asbestos

Customer Pro	oject:	GP Leaf River New Augusta, N	/IS	CA Labs Project #:	CBR22118602
Sample #	Layer #	Analysts Physical Description of Subsample	Asbestos type / calibrated visual estimate percent	List of Affe	ected Building ial Types
1	1-1	White Sealant	3% Chrysotile	White Se	alant
2	2-1	White Sealant	3% Chrysotile	-	
3	3-1	White Sealant	3% Chrysotile	-	
4	4-1	White Sealant	3% Chrysotile	_	

Glossary of abbreviations (non-asbestos fibers and non-fibrous minerals):

ca - carbonate gypsum - gypsum bi - binder or - organic ma - matrix mi - mica ve - vermiculite

ot - other

pe - perlite qu - quartz

fg - fiberglass

mw - mineral wool wo - wollastinite la - talc

sy - synthelic ce - cellulose br - brucite

ka - kaolin (clay)

pa - palygorskite (clay)

This report relates to the items tested. This report is not to be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST, AIHA LAP, LLC, or any other agency of the federal government. This report may not be reproduced except in full without written permission from CA Labs. These results are submitted pursuant to CA Labs' current terms and sale, condition of sale, including the company's standard warranty and limitations of liability provisions and no responsibility or liability is assumed for the manner in which the results are used or interpreted. Unless notified in writing to return the samples covered by this report, CA Labs will store the samples for a period of ninety (90) days before discarding. A shipping or handling fee may be assessed for the return of any samples.

Dedicated to Quality

CA Labs, L.L.C.

12232 Industriplex, Suite 32 Baton Rouge, LA 70809 Phone 225-751-5632 Fax 225-751-5634



NVLAP #200772-0 TDSHS #300370 **CDPHE #AL-18111**

Polarized Light Asbestiform Materials Characterization

(Y/N)

Ν

Υ

Attn: Joseph Lambert **Customer Info:** Industrial Asbestos Removal, LLC

Customer Project: GP Leaf River New Augusta, CA Labs Project #: CBR22118602

11637 Sunbelt Court Baton Rouge, LA 70809

Sample #

Turnaround Time: 24 hr

11/8/2022 Date: 11/8/2022 Samples Received: 11/4/2022 Date Of Sampling:

Phone # 225-752-2194 225-752-1686 Fax# Layer Com

ment

Homo-Analysts Physical Description of geneo Subsample us

Non-asbestos fiber Asbestos type / type / percent calibrated visual estimate percent

Purchase Order #: Non-fibrous type / percent

70-1412

1-1

3% Chrysotile

97% qu, ma, bi

Black Tar and Felt

White Sealant

None Detected

20% ce

80% qu, ma, bi

Yellow Insulation 1-3

None Detected Y

100% fg

White Sealant

3% Chrysotile

97% qu, ma, bi

Black Tar and Felt 2-2

None Detected

20% ce

80% qu, ma, bi

Yellow Insulation 2-3

None Detected

100% fg

White Sealant 3-1

3% Chrysotile

97% qu, ma, bi

Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116) Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate gypsum - gypsum mi - mica ve - vermiculite

fg - fiberglass mw - mineral wool

ce - cellulose br - brucite ka - kaolin (clay)

bi - binder or - organic ma - matrix ot -other pe - perlite qu - quartz wo - wollastinite ta - talc sy - synthetic

pa - palygorskite (clay)

Approved Signatories:

John Grout Analyst

Senior Analyst Alicia Stretz

Laboratory Director Chris Williams

Anthophyllite in association with Fibrous Tale

^{1.} Fire Damage significant fiber damage - reported percentages reflect unaltered fibers

Fire Damage significant riber damages effecting librous percentages
 Actinolite in association with Vermiculite

Layer not analyzed - attached to previous positive layer and contamination is suspected

^{5.} Not enough sample to analyze

Amanganyme in association with reduces the
 Contamination suspected from other building materials
 Favorable scenario for water separation on vermiculite for possible analysis by another method

^{9 &}lt; 1% Result point counted positive 10 TEM analysis suggested

Dedicated to Quality

CA Labs, L.L.C.

12232 Industriplex, Suite 32 Baton Rouge, LA 70809 Phone 225-751-5632 Fax 225-751-5634



NVLAP #200772-0 TDSHS #300370 **CDPHE #AL-18111** LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Joseph Lambert **Customer Project:** CA Labs Project #: Industrial Asbestos Removal, LLC GP Leaf River New Augusta, CBR22118602 11637 Sunbelt Court Baton Rouge, LA 70809 Date: 11/8/2022 Turnaround Time: 24 hr Samples Received: 11/8/2022 Phone # 225-752-2194 Date Of Sampling: 11/4/2022 Fax# 225-752-1686 Purchase Order #: 70-1412 Sample # Com Layer Analysts Physical Description of Homo-Asbestos type / Non-asbestos fiber Non-fibrous type ment # Subsample geneo calibrated visual type / percent / percent estimate percent US (Y/N) Black Tar and Felt 3-2 N None Detected 20% ce 80% qu, ma, bi Yellow Insulation None Detected 100% fa White Sealant Y 3% Chrysotile 97% qu, ma, bi Black Tar and Felt N None Detected 20% ce 80% qu, ma, bi Yellow Insulation None Detected 100% fg

> Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116) Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate gypsum - gypsum bi - binder

or - organic

ma - matrix

mi - mica ve - vermiculite ot -other pe - perlite

au - auartz

fg - fiberglass mw - mineral wool wo - wollastinite

ta - talc sy - synthetic ce - cellulose br - brucite

ka - kaolin (clay) pa - palygorskite (clay)

Approved Signatories:

John Grout Analyst

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers

2. Fire Damage no significant fiber damages effecting fibrous percentages

3. Actinolite in association with Vermiculite

4. Layer not analyzed - attached to previous positive layer and contamination is suspected

5. Not enough sample to analyze

Senior Analyst Alicia Stretz

Laboratory Director Chris Williams

Aris hall

6 Anthophyllite in association with Fibrous Talc

Contamination suspected from other building materials

8. Favorable scenario for water separation on vermiculite for possible analysis by another method

Classification for water separate
 Classification for water se