

**STATE OF MISSISSIPPI
AIR POLLUTION CONTROL
TITLE V PERMIT**

TO OPERATE AIR EMISSIONS EQUIPMENT

THIS CERTIFIES THAT

Gulf South Pipeline Company LLC, Petal Compressor Station
1382 Highway 11 North
Petal, Mississippi
Forrest County

has been granted permission to operate air emissions equipment in accordance with emission limitations, monitoring requirements and conditions set forth herein. This permit is issued in accordance with Title V of the Federal Clean Air Act (42 U.S.C.A. § 7401 - 7671) and the provisions of the Mississippi Air and Water Pollution Control Law (Section 49-17-1 et. seq., Mississippi Code of 1972), and the regulations and standards adopted and promulgated thereunder.

Permit Issued: Sep 24, 2018

Permit Modified: Sep 03, 2019

Permit Modified: JAN 23 2020 (Name Change)

Effective Date: As specified herein.

MISSISSIPPI ENVIRONMENTAL QUALITY PERMIT BOARD



AUTHORIZED SIGNATURE

MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY

Expires: Aug 31, 2023

Permit No.: 0800-00050

TABLE OF CONTENTS

SECTION 1.	GENERAL CONDITIONS	3
SECTION 2.	EMISSION POINTS & POLLUTION CONTROL DEVICES.....	13
SECTION 3.	EMISSION LIMITATIONS & STANDARDS.....	16
SECTION 4.	COMPLIANCE SCHEDULE	33
SECTION 5.	MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS	34
SECTION 6.	ALTERNATIVE OPERATING SCENARIOS.....	48
SECTION 7.	TITLE VI REQUIREMENTS	49

APPENDIX A LIST OF ABBREVIATIONS USED IN THIS PERMIT

APPENDIX B LIST OF REGULATIONS REFERENCED IN THIS PERMIT

SECTION 1. GENERAL CONDITIONS

- 1.1 The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the Federal Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(a).)
- 1.2 It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(b).)
- 1.3 This permit and/or any part thereof may be modified, revoked, reopened, and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(c).)
- 1.4 Prior to its expiration, this permit may be reopened in accordance with the provisions listed below.
 - (a) This permit shall be reopened and revised under any of the following circumstances:
 - (1) Additional applicable requirements under the Federal Act become applicable to a major Title V source with a remaining permit term of 3 or more years. Such a reopening shall be completed no later than 18 months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended.
 - (2) Additional requirements (including excess emissions requirements) become applicable to an affected source under the acid rain program. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the permit.
 - (3) The Permit Board or EPA determines that the permit contains a material mistake or that inaccurate statements were made in establishing the emission standards or other terms or conditions of the permit.
 - (4) The Administrator or the Permit Board determines that the permit must be revised or revoked to assure compliance with the applicable requirements.
 - (b) Proceedings to reopen and issue this permit shall follow the same procedures as apply

to initial permit issuance and shall only affect those parts of the permit for which cause to reopen exists. Such reopening shall be made as expeditiously as practicable.

- (c) Reopenings shall not be initiated before a notice of such intent is provided to the Title V source by the DEQ at least 30 days in advance of the date that the permit is to be reopened, except that the Permit Board may provide a shorter time period in the case of an emergency.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.G)

- 1.5 The permittee shall furnish to the DEQ within a reasonable time any information the DEQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the DEQ copies of records required to be kept by the permittee or, for information to be confidential, the permittee shall furnish such records to DEQ along with a claim of confidentiality. The permittee may furnish such records directly to the Administrator along with a claim of confidentiality. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(e).)
- 1.6 This permit does not convey any property rights of any sort, or any exclusive privilege. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(6)(d).)
- 1.7 The provisions of this permit are severable. If any provision of this permit, or the application of any provision of this permit to any circumstances, is challenged or held invalid, the validity of the remaining permit provisions and/or portions thereof or their application to other persons or sets of circumstances, shall not be affected thereby. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(5).)
- 1.8 The permittee shall pay to the DEQ an annual permit fee. The amount of fee shall be determined each year based on the provisions of regulated pollutants for fee purposes and the fee schedule specified in the Commission on Environmental Quality's order which shall be issued in accordance with the procedure outlined in Regulation 11 Miss. Admin. Code Pt. 2, Ch. 6.
 - (a) For purposes of fee assessment and collection, the permittee shall elect for actual or allowable emissions to be used in determining the annual quantity of emissions unless the Commission determines by order that the method chosen by the applicant for calculating actual emissions fails to reasonably represent actual emissions. Actual emissions shall be calculated using emission monitoring data or direct emissions measurements for the pollutant(s); mass balance calculations such as the amounts of the pollutant(s) entering and leaving process equipment and where mass balance calculations can be supported by direct measurement of process parameters, such direct measurement data shall be supplied; published emission factors such as those relating release quantities to throughput or equipment type (e.g., air emission factors); or other approaches such as engineering calculations (e.g., estimating volatilization using

published mathematical formulas) or best engineering judgments where such judgments are derived from process and/or emission data which supports the estimates of maximum actual emission. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.A(2).)

- (b) If the Commission determines that there is not sufficient information available on a facility's emissions, the determination of the fee shall be based upon the permitted allowable emissions until such time as an adequate determination of actual emissions is made. Such determination may be made anytime within one year of the submittal of actual emissions data by the permittee. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.A(2).) If at any time within the year the Commission determines that the information submitted by the permittee on actual emissions is insufficient or incorrect, the permittee will be notified of the deficiencies and the adjusted fee schedule. Past due fees from the adjusted fee schedule will be paid on the next scheduled quarterly payment time. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.D(2).)
 - (c) The fee shall be due September 1 of each year. By July 1 of each year the permittee shall submit an inventory of emissions for the previous year on which the fee is to be assessed. The permittee may elect a quarterly payment method of four (4) equal payments; notification of the election of quarterly payments must be made to the DEQ by the first payment date of September 1. The permittee shall be liable for penalty as prescribed by State Law for failure to pay the fee or quarterly portion thereof by the date due. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.D.)
 - (d) If in disagreement with the calculation or applicability of the Title V permit fee, the permittee may petition the Commission in writing for a hearing in accordance with State Law. Any disputed portion of the fee for which a hearing has been requested will not incur any penalty or interest from and after the receipt by the Commission of the hearing petition. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.6.C.)
- 1.9 No permit revision shall be required under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes for changes that are provided for in this permit. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(8).)
- 1.10 Any document required by this permit to be submitted to the DEQ shall contain a certification by a responsible official that states that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.2.E.)
- 1.11 The permittee shall allow the DEQ, or an authorized representative, upon the presentation of credentials and other documents as may be required by law, to perform the following:
- (a) enter upon the permittee's premises where a Title V source is located or emissions-related activity is conducted, or where records must be kept under the conditions of this permit;

- (b) have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
- (d) as authorized by the Federal Act, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.C(2).)

- 1.12 Except as otherwise specified or limited herein, the permittee shall have necessary sampling ports and ease of accessibility for any new air pollution control equipment, obtained after May 8, 1970, and vented to the atmosphere. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.I(1).)
- 1.13 Except as otherwise specified or limited herein, the permittee shall provide the necessary sampling ports and ease of accessibility when deemed necessary by the Permit Board for air pollution control equipment that was in existence prior to May 8, 1970. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.I(2).)
- 1.14 Compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance where such applicable requirements are included and are specifically identified in the permit or where the permit contains a determination, or summary thereof, by the Permit Board that requirements specifically identified previously are not applicable to the source. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.F(1).)
- 1.15 Nothing in this permit shall alter or affect the following:
 - (a) the provisions of Section 303 of the Federal Act (emergency orders), including the authority of the Administrator under that section;
 - (b) the liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance;
 - (c) the applicable requirements of the acid rain program, consistent with Section 408(a) of the Federal Act.
 - (d) the ability of EPA to obtain information from a source pursuant to Section 114 of the Federal Act.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.F(2).)

- 1.16 The permittee shall comply with the requirement to register a Risk Management Plan if permittee's facility is required pursuant to Section 112(r) of the Act to register such a plan. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.H.)
- 1.17 Expiration of this permit terminates the permittee's right to operate unless a timely and complete renewal application has been submitted. A timely application is one which is submitted at least six (6) months prior to expiration of the Title V permit. If the permittee submits a timely and complete application, the failure to have a Title V permit is not a violation of regulations until the Permit Board takes final action on the permit application. This protection shall cease to apply if, subsequent to the completeness determination, the permittee fails to submit by the deadline specified in writing by the DEQ any additional information identified as being needed to process the application. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.C(2)., R. 6.4.B., and R. 6.2.A(1)(c).)
- 1.18 The permittee is authorized to make changes within their facility without requiring a permit revision (ref: Section 502(b)(10) of the Act) if:
- (a) the changes are not modifications under any provision of Title I of the Act;
 - (b) the changes do not exceed the emissions allowable under this permit;
 - (c) the permittee provides the Administrator and the Department with written notification in advance of the proposed changes (at least seven (7) days, or such other time frame as provided in other regulations for emergencies) and the notification includes:
 - (1) a brief description of the change(s),
 - (2) the date on which the change will occur,
 - (3) any change in emissions, and
 - (4) any permit term or condition that is no longer applicable as a result of the change;
 - (d) the permit shield shall not apply to any Section 502(b)(10) change.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.F(1).)

- 1.19 Should the Executive Director of the Mississippi Department of Environmental Quality declare an Air Pollution Emergency Episode, the permittee will be required to operate in accordance with the permittee's previously approved Emissions Reduction Schedule or, in the absence of an approved schedule, with the appropriate requirements specified in 11

Miss. Admin. Code Pt. 2, Ch. 3., "Regulations for the Prevention of Air Pollution Emergency Episodes" for the level of emergency declared. (Ref.: 11 Miss. Admin. Code Pt. 2, Ch. 3.)

- 1.20 Except as otherwise provided herein, a modification of the facility may require a Permit to Construct in accordance with the provisions of Regulations 11 Miss. Admin. Code Pt. 2, Ch. 2., "Permit Regulations for the Construction and/or Operation of Air Emissions Equipment", and may require modification of this permit in accordance with Regulations 11 Miss. Admin. Code Pt. 2, Ch. 6., "Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act". Modification is defined as "[a]ny physical change in or change in the method of operation of a facility which increases the actual emissions or the potential uncontrolled emissions of any air pollutant subject to regulation under the Federal Act emitted into the atmosphere by that facility or which results in the emission of any air pollutant subject to regulation under the Federal Act into the atmosphere not previously emitted. A physical change or change in the method of operation shall not include:
- (a) routine maintenance, repair, and replacement;
 - (b) use of an alternative fuel or raw material by reason of an order under Sections 2 (a) and (b) of the Federal Energy Supply and Environmental Coordination Act of 1974 (or any superseding legislation) or by reason of a natural gas curtailment plan pursuant to the Federal Power Act;
 - (c) use of an alternative fuel by reason of an order or rule under Section 125 of the Federal Act;
 - (d) use of an alternative fuel or raw material by a stationary source which:
 - (1) the source was capable of accommodating before January 6, 1975, unless such change would be prohibited under any federally enforceable permit condition which was established after January 6, 1975, pursuant to 40 CFR 52.21 or under regulations approved pursuant to 40 CFR 51.166; or
 - (2) the source is approved to use under any permit issued under 40 CFR 52.21 or under regulations approved pursuant to 40 CFR 51.166;
 - (e) an increase in the hours of operation or in the production rate unless such change would be prohibited under any federally enforceable permit condition which was established after January 6, 1975, pursuant to 40 CFR 52.21 or under regulations approved pursuant to 40 CFR Subpart I or 40 CFR 51.166; or
 - (f) any change in ownership of the stationary source.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 2.1.C(15).)

- 1.21 Any change in ownership or operational control must be approved by the Permit Board. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.4.D(4).)
- 1.22 This permit is a Federally approved operating permit under Title V of the Federal Clean Air Act as amended in 1990. All terms and conditions, including any designed to limit the source's potential to emit, are enforceable by the Administrator and citizens under the Federal Act as well as the Commission. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.B(1).)
- 1.23 Except as otherwise specified or limited herein, the open burning of residential, commercial, institutional, or industrial solid waste, is prohibited. This prohibition does not apply to infrequent burning of agricultural wastes in the field, silvicultural wastes for forest management purposes, land-clearing debris, debris from emergency clean-up operations, and ordnance. Open burning of land-clearing debris must not use starter or auxiliary fuels which cause excessive smoke (rubber tires, plastics, etc.); must not be performed if prohibited by local ordinances; must not cause a traffic hazard; must not take place where there is a High Fire Danger Alert declared by the Mississippi Forestry Commission or Emergency Air Pollution Episode Alert imposed by the Executive Director and must meet the following buffer zones.
- (a) Open burning without a forced-draft air system must not occur within 500 yards of an occupied dwelling.
 - (b) Open burning utilizing a forced-draft air system on all fires to improve the combustion rate and reduce smoke may be done within 500 yards of but not within 50 yards of an occupied dwelling.
 - (c) Burning must not occur within 500 yards of commercial airport property, private air fields, or marked off-runway aircraft approach corridors unless written approval to conduct burning is secured from the proper airport authority, owner or operator.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.G.)

- 1.24 Except as otherwise specified herein, the permittee shall be subject to the following provision with respect to emergencies:
- (a) Except as otherwise specified herein, an "emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventative maintenance, careless or

improper operation, or operator error.

- (b) An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions specified in (c) following are met.
- (c) The affirmative defense of emergency shall be demonstrated through properly signed contemporaneous operating logs, or other relevant evidence that include information as follows:
 - (1) an emergency occurred and that the permittee can identify the cause(s) of the emergency;
 - (2) the permitted facility was at the time being properly operated;
 - (3) during the period of the emergency the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other requirements in the permit; and
 - (4) the permittee submitted notice of the emergency to the DEQ within 2 working days of the time when emission limitations were exceeded due to the emergency. This notice must contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.
- (d) In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (e) This provision is in addition to any emergency or upset provision contained in any applicable requirement specified elsewhere herein.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.G.)

1.25 Except as otherwise specified herein, the permittee shall be subject to the following provisions with respect to upsets, startups, and shutdowns.

- (a) Upsets (as defined in 11 Miss. Admin. Code Pt. 2, R. 1.2.)
 - (1) For an upset, the Commission may pursue an enforcement action for noncompliance with an emission standard or other requirement of an applicable rule, regulation, or permit. In determining whether to pursue enforcement action, and/or the appropriate enforcement action to take, the Commission may consider whether the source has demonstrated through properly signed contemporaneous operating logs or other relevant evidence

the following:

- (i) An upset occurred and that the source can identify the cause(s) of the upset;
 - (ii) The source was at the time being properly operated;
 - (iii) During the upset the source took all reasonable steps to minimize levels of emissions that exceeded the emission standard or other requirement of an applicable rule, regulation, or permit;
 - (iv) That within 5 working days of the time the upset began, the source submitted a written report to the Department describing the upset, the steps taken to mitigate excess emissions or any other noncompliance, and the corrective actions taken and;
 - (v) That as soon as practicable but no later than 24 hours of becoming aware of an upset that caused an immediate adverse impact to human health or the environment beyond the source boundary or caused a general nuisance to the public, the source provided notification to the Department.
- (2) In any enforcement proceeding by the Commission, the source seeking to establish the occurrence of an upset has the burden of proof.
 - (3) This provision is in addition to any upset provision contained in any applicable requirement.
 - (4) These upset provisions apply only to enforcement actions by the Commission and are not intended to prohibit EPA or third party enforcement actions.
- (b) Startups and Shutdowns (as defined in 11 Miss. Admin. Code Pt. 2, R. 1.2.)
- (1) Startups and shutdowns are part of normal source operation. Emission limitations apply during startups and shutdowns unless source specific emission limitations or work practice standards for startups and shutdowns are defined by an applicable rule, regulation, or permit.
 - (2) Where the source is unable to comply with existing emission limitations established under the State Implementation Plan (SIP) and defined in this regulation, 11 Mississippi Administrative Code, Part 2, Chapter 1, the Department will consider establishing source specific emission limitations or work practice standards for startups and shutdowns. Source specific emission

limitations or work practice standards established for startups and shutdowns are subject to the requirements prescribed in 11 Miss. Admin. Code Pt. 2, R. 1.10.B(2)(a) through (e).

- (3) Where an upset as defined in Rule 1.2 occurs during startup or shutdown, see the upset requirements above.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.10.)

- 1.26 The permittee shall comply with all applicable standards for demolition and renovation activities pursuant to the requirements of 40 CFR Part 61, Subpart M, as adopted by reference in Regulation 11 Miss Admin. Code Pt. 2, R. 1.8. The permittee shall not be required to obtain a modification of this permit in order to perform the referenced activities. (Ref.: 11 Miss Admin. Code Pt. 2, R. 1.8.)

SECTION 2. EMISSION POINTS & POLLUTION CONTROL DEVICES

Emission Point	Description
AA-001	2,587 HP Waukesha Model 12VAT25GL four stroke lean burn (4SLB) spark ignition (SI) natural gas-fired compressor engine (Facility Ref. HGS)
AA-002	2,587 HP Waukesha Model 12VAT25GL 4SLB SI natural gas-fired compressor engine (Facility Ref. HGS)
AA-003	2,587 HP Waukesha Model 12VAT25GL 4SLB SI natural gas-fired compressor engine (Facility Ref. HGS)
AA-004	1.5 MMBTUH natural gas-fired Glycol Reboiler No. 1 (Facility Ref. HGS)
AA-005	1.5 MMBTUH natural gas-fired Glycol Reboiler No. 2 (Facility Ref. HGS)
AA-006	0.5 MMBTUH natural gas-fired Glycol Reboiler No. 3 (Facility Ref. HGS)
AA-007	1.3 MMBTUH natural gas-fired Glycol Reboiler No. 4 (Facility Ref. HGS)
AA-008	1,478 HP Waukesha Model 7042GL 4SLB SI natural gas-fired compressor engine (Facility Ref. HGS)
AA-014	Regenerator Still Vent No. 1 (Facility Ref. HGS)
AA-015	Regenerator Still Vent No. 2 (Facility Ref. HGS)
AA-016	Regenerator Still Vent No. 3 (Facility Ref. HGS)
AA-017	Regenerator Still Vent No. 4 (Facility Ref. HGS)
AA-018	200 HP John Deere Model 6076 compression ignition (CI) diesel-fired emergency power generator engine (Facility Ref. HGS)
AB-001	2,087 HP Waukesha Model 8LAT27GL 4SLB SI natural gas-fired compressor engine (Facility Ref. PGS)
AB-002	2,087 HP Waukesha Model 8LAT27GL 4SLB SI natural gas-fired compressor engine (Facility Ref. PGS)
AB-003	2,087 HP Waukesha Model 8LAT27GL 4SLB SI natural gas-fired compressor engine (Facility Ref. PGS)
AB-004	2,087 HP Waukesha Model 8LAT27GL 4SLB SI natural gas-fired compressor engine (Facility Ref. PGS)
AB-005	2,087 HP Waukesha Model 8LAT27GL 4SLB SI natural gas-fired compressor engine (Facility Ref. PGS)
AB-006	1.7 MMBTUH natural gas-fired Petal I Line Heater (Facility Ref. PGS)

Emission Point	Description
AB-007	1.4 MMBTUH natural gas-fired Petal II Glycol Reboiler (Facility Ref. PGS)
AB-008	280 HP Cummins Model GTA12 4SLB SI natural gas-fired emergency power generator engine (Facility Ref. PGS)
AB-009	3.0 MMBTUH Emergency Flare (Facility Ref. PGS)
AB-010	1.5 MMBTUH natural gas-fired Petal I Glycol Reboiler (Facility Ref. PGS)
AB-011	15 MMBTUH natural gas-fired Petal II Line Heater (Facility Ref. PGS)
AB-012	15 MMBTUH natural gas-fired Petal II Line Heater (Facility Ref. PGS)
AB-013	456 HP Cummins Model GTA19 4SLB SI natural gas-fired emergency power generator engine (Facility Ref. PGS)
AB-015	Regenerator Still Vent No. 1 (Facility Ref. PGS)
AB-016	Regenerator Still Vent No. 2 (Facility Ref. PGS)
AB-017	Regenerator Still Vent No. 3 (Facility Ref. PGS) with emissions routed to AB-028
AB-018	17 HP Cummins Model 15JC four stroke rich burn (4SRB) SI natural gas-fired emergency power generator engine at Natural Gas Cavern No. 3 (Facility Ref. PGS)
AB-019	1.8 MMBTUH natural gas-fired Petal III Glycol Reboiler No. 3 (Facility Ref. PGS)
AB-020	1,334 HP Cummins Model GTA19 4SLB SI natural gas-fired emergency power generator engine (Facility Ref. PGS)
AB-021	50 MMBTUH natural gas-fired Hot Oil Heater (Facility Ref. PGS)
AB-022	50 MMBTUH natural gas-fired Hot Oil Heater (Facility Ref. PGS)
AB-023	40 HP Sentry Pro Model SP-300-44 4SLB SI propane-fired emergency power generator engine at Cavern No. 8
AB-024	40 HP Sentry Pro Model SP-300-44 4SLB SI propane-fired emergency power generator engine at the Communications Building
AB-025	48 HP Sentry Pro Model SP-250-60 4SRB SI propane-fired emergency power generator engine at Cavern No. 12A
AB-026	5.0 MMBTUH natural gas-fired Petal 3 Glycol Reboiler No. 2
AB-027	Petal 3 Regenerator Still Vent No. 2 with emissions routed to AB-028
AB-028	Thermal Oxidizer controlling emissions from AB-017 and AB-027
AB-029	Electric driven reciprocating compressor engine No. 1

Emission Point	Description
AB-030	Electric driven reciprocating compressor engine No. 2
AB-031	Facility-wide fugitive emissions

SECTION 3. EMISSION LIMITATIONS & STANDARDS

A. Facility-Wide Emission Limitations & Standards

3.A.1 Except as otherwise specified or limited herein, the permittee shall not cause, permit, or allow the emission of smoke from a point source into the open air from any manufacturing, industrial, commercial or waste disposal process which exceeds forty (40) percent opacity subject to the exceptions provided in (a) & (b).

- (a) Startup operations may produce emissions which exceed 40% opacity for up to fifteen (15) minutes per startup in any one hour and not to exceed three (3) startups per stack in any twenty-four (24) hour period.
- (b) Emissions resulting from soot blowing operations shall be permitted provided such emissions do not exceed 60 percent opacity, and provided further that the aggregate duration of such emissions during any twenty-four (24) hour period does not exceed ten (10) minutes per billion BTU gross heating value of fuel in any one hour.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.A.)

3.A.2 Except as otherwise specified or limited herein, the permittee shall not cause, allow, or permit the discharge into the ambient air from any point source or emissions, any air contaminant of such opacity as to obscure an observer's view to a degree in excess of 40% opacity, equivalent to that provided in Paragraph 3.A.1. This shall not apply to vision obscuration caused by uncombined water droplets. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.B.)

B. Emission Point Specific Emission Limitations & Standards

Emission Point(s)	Applicable Requirement	Condition Number(s)	Pollutant/Parameter	Limit/Standard
AA-001, AA-002, AA-003, AA-008, AB-001 through AB-005, AB-011, AB-012, AB-020, AB-021, and AB-022	11 Miss. Admin. Code Pt. 2, R. 1.3. D(1)(b)	3.B.1	PM	$E=0.8808*(I)^{-0.1667}$
AA-004 through AA-007, AA-018, AB-006 through AB-010, AB-013, AB-018, AB-019, AB-023, AB-024, AB-025, and AB-026	11 Miss. Admin. Code Pt. 2, R. 1.3. D(1)(a)	3.B.2	PM	0.6 lb/MMBTU
AA-004 through AA-007, AB-006, AB-007, AB-010 through AB-012, AB-019, AB-021, AB-022 and AB-026	11 Miss. Admin. Code Pt. 2, R. 1.4.A(1)	3.B.3	SO ₂	4.8 lbs/MMBTU
AA-001 through AA-003	Air Title V Permit No. 0800-00050 issued April 02, 2008	3.B.4	NO _x	10.38 lbs/hr from each emission unit

Emission Point(s)	Applicable Requirement	Condition Number(s)	Pollutant/Parameter	Limit/Standard
		3.B.5	CO	12.83 lbs/hr from each emission unit
AA-001, AA-002, AA-003, AA-008, and AB-001 through AB-005	Air Title V Permit No. 0800-00050 issued April 02, 2008	3.B.6	NO _x	109.3 tons/year combined
		3.B.7	CO	184.9 tons/year combined
AA-008	Air Title V Permit No. 0800-00050 issued April 02, 2008	3.B.8	NO _x	5.93 lbs/hr
		3.B.9	CO	7.33 lbs/hr
AB-001 through AB-005	Air Title V Permit No. 0800-00050 issued April 02, 2008	3.B.10	NO _x	5.11 lbs/hr from each emission unit
		3.B.11	CO	10.35 lbs/hr from each emission unit
AA-001 through AA-003, AA-008, AA-018, AB-001 through AB-005, AB-008, AB-013, AB-018, AB-020, and AB-023 through AB-025	NESHAP for Stationary Reciprocating Internal Combustion Engines (RICE), 40 CFR Part 63, Subpart ZZZZ 40 CFR Part 63.6580, 40 CFR Part 63.6585(a) and (c), 40 CFR Part 63.6590(a)(1)(iii), and 40 CFR Part 63.6590(c)(1)	3.B.12	HAP	MACT applicability
AA-001 through AA-003, AA-008, and AB-001 through AB-005	40 CFR Part 63.6603(a), 40 CFR Part 63.6625(j), and Item and Footnote 1 of Table 2d of 40 CFR Part 63, Subpart ZZZZ	3.B.13	HAP	Scheduled Maintenance Activities
AB-008, AB-013, AB-018, AB-020, AB-023, and AB-024	40 CFR Part 63.6603(a), 40 CFR Part 63.6625(j), and Item 5 and Footnotes 1 and 2 of Table 2d of 40 CFR Part 63, Subpart ZZZZ	3.B.14	HAP	Scheduled Maintenance Activities
AA-018	40 CFR Part 63.6603(a), 40 CFR Part 63.6625(i), and Item 4 and Footnotes 1 and 2 of	3.B.15	HAP	Scheduled Maintenance Activities

Emission Point(s)	Applicable Requirement	Condition Number(s)	Pollutant/Parameter	Limit/Standard
	Table 2d of 40 CFR Part 63, Subpart ZZZZ			
AA-001 through AA-003, AA-008, AA-018, and AB-001 through AB-005, AB-008, AB-013, AB-018, AB-020, AB-023, and AB-024	40 CFR Part 63.6605	3.B.16	HAP	General Compliance
	40 CFR Part 63.6625(e)(3) and Item 9 of Table 6 of 40 CFR Part 63, Subpart ZZZZ	3.B.17	HAP	General Operating Requirements
AA-018, AB-008, AB-013, AB-018, AB-020, AB-023, and AB-024	40 CFR Part 63.6625(f)	3.B.18	HAP	General Operating Requirements
	40 CFR Part 63.6625(h)	3.B.19	HAP	General Operating Requirements
AB-025	NSPS for Stationary Spark Ignition Internal Combustion Engines, 40 CFR Part 60, Subpart JJJJ 40 CFR Part 60.4230(a)(4)(iv)	3.B.20	NO _x , CO, and VOC	Applicability
	40 CFR Part 60.4233(c) and 40 CFR Part 60.4234	3.B.21	NO _x , CO, and VOC	General Operating Requirements
AB-017, AB-027, and AB-028	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	3.B.22	VOC and HAP	Operational Restriction
AB-028	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	3.B.23	Operating Restriction	General Operating Requirement
AB-029, AB-030, and AB-031	NSPS for Crude Oil and Natural Gas Facilities for which Construction, Modification or Reconstruction Commenced After September 18, 2015, 40 CFR Part 60, Subpart OOOOa 40 CFR 60.5360a, Subpart OOOOa and 40 CFR 60.5365a(c) and (j), Subpart OOOOa and 40 CFR 60.5370a(a) and (b), Subpart OOOOa	3.B.24	VOC	NSPS Applicability
	40 CFR 60.5370a(a) and (b), Subpart OOOOa	3.B.25	VOC	Continuous Compliance

- 3.B.1 For Emission Points AA-001, AA-002, AA-003, AA-008, AB-001 through AB-005, AB-011, AB-012, AB-020, AB-021, and AB-022, the maximum permissible emission of ash and/or particulate matter from fossil fuel burning installations greater than 10 million BTU per hour heat input but less than 10,000 million BTU per hour heat input shall not exceed an emission rate as determined by the relationship

$$E=0.8808*(I)^{-0.1667}$$

Where E is the emission rate in pounds per million BTU per hour heat input and I is the heat input in millions of BTU per hour. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3. D(1)(b))

- 3.B.2 For Emission Points AA-004 through AA-007, AA-018, AB-006 through AB-010, AB-013, AB-018, AB-019, AB-023, AB-024, AB-025, and AB-026, the maximum permissible emission of ash and/or particulate matter from a fossil fuel burning installations of less than 10 million BTU per hour heat input shall not exceed 0.6 pounds per million BTU per hour heat input. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3. D(1)(a))
- 3.B.3 For Emission Points AA-004 through AA-007, AB-006, AB-007, AB-010 through AB-012, AB-019, AB-021, AB-022, and AB-026, the maximum discharge of sulfur oxides from any fuel burning installation in which the fuel is burned primarily to produce heat or power by indirect heat transfer shall not exceed 4.8 pounds (measured as sulfur dioxide) per million BTU heat input. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.4.A(1))
- 3.B.4 For Emission Point AA-001, AA-002, and AA-003, the permittee shall not cause to be discharged into the atmosphere any gases which contain nitrogen oxides in excess of 10.38 pounds per hour (lb/hr). (Ref.: Air Title V Permit No. 0800-00050 issued April 02, 2008)
- 3.B.5 For Emission Point AA-001, AA-002, and AA-003, the permittee shall not cause to be discharged into the atmosphere any gases which contain carbon monoxide in excess of 12.83 lb/hr. (Ref.: Air Title V Permit No. 0800-00050 issued April 02, 2008)
- 3.B.6 For Emission Points AA-001, AA-002, AA-003, AA-008, AB-001, AB-002, AB-003, AB-004, and AB-005, the permittee shall not emit more than 109.3 tons per year (tpy) of nitrogen oxides. (Ref.: Air Title V Permit No. 0800-00050 issued April 02, 2008)
- 3.B.7 For Emission Points AA-001, AA-002, AA-003, AA-008, AB-001, AB-002, AB-003, AB-004, and AB-005, the permittee shall not emit more than 184.9 tpy of carbon monoxide. (Ref.: Air Title V Permit No. 0800-00050 issued April 02, 2008)
- 3.B.8 For Emission Point AA-008, the permittee shall not cause to be discharged into the atmosphere any gases which contain nitrogen oxides in excess of 5.93 lb/hr. (Ref.: Air Title V Permit No. 0800-00050 issued April 02, 2008)

- 3.B.9 For Emission Point AA-008, the permittee shall not cause to be discharged into the atmosphere any gases which contain carbon monoxide in excess of 7.33 lb/hr. (Ref.: Air Title V Permit No. 0800-00050 issued April 02, 2008)
- 3.B.10 For Emission Points AB-001 through AB-005, the permittee shall not cause to be discharged into the atmosphere any gases which contain nitrogen oxides in excess of 5.11 lb/hr. (Ref.: Air Title V Permit No. 0800-00050 issued April 02, 2008)
- 3.B.11 For Emission Points AB-001 through AB-005, the permittee shall not cause to be discharged into the atmosphere any gases which contain carbon monoxide in excess of 10.35 lb/hr. (Ref.: Air Title V Permit No. 0800-00050 issued April 02, 2008)
- 3.B.12 For Emission Points AA-001, AA-002, AA-003, AA-008, AA-018, AB-001 through AB-005, AB-008, AB-013, AB-018, AB-020, AB-023, AB-024, and AB-025, the permittee is subject to the National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (RICE), 40 CFR Part 63, Subpart ZZZZ.

Emission Points AA-001, AA-002, AA-003, AA-008, and AB-001 through AB-005 are existing non-emergency spark ignition (SI) four stroke lean burn (4SLB) Remote engines with a site rating of more than 500 brake HP located at an Area source of HAP emissions and as such are required to meet the operational requirements of 40 CFR Part 63, Subpart ZZZZ and the General Provisions in Subpart A.

Emission Points AB-008, AB-013, AB-018, AB-020, AB-023, and AB-024 are existing emergency SI RICE that operate as emergency backup power generator engines located at an Area source of HAP emissions and as such are required to meet the operational requirements of 40 CFR Part 63, Subpart ZZZZ and the General Provisions in Subpart A.

Emission Point AA-018 is an existing emergency compression ignition (CI) RICE that operates as an emergency backup power generator engine with a site rating of less than 500 brake HP located at an Area source of HAP emissions and as such is required to meet the operational requirements of 40 CFR Part 63, Subpart ZZZZ and the General Provisions in Subpart A.

Emission Point AB-025 is a new emergency SI 4SLB propane-fired stationary RICE with a site rating of less than 500 brake HP located at an Area source of HAP emissions. As such, the emergency engine must meet the requirements of 40 CFR Part 63, Subpart ZZZZ, by meeting the requirements of 40 CFR Part 60, Subpart JJJJ. No further requirements apply for such engines under 40 CFR Part 63, Subpart ZZZZ, or the General Provisions in Subpart A.

(Ref.: 40 CFR Part 63.6580, 40 CFR Part 63.6585(a) and (c), 40 CFR Part 63.6590(a)(1)(iii), and 40 CFR Part 63.6590(c)(1))

3.B.13 For Emission Points AA-001 through AA-003, AA-008, and AB-001 through AB-005, the permittee shall comply with the following requirements:

- (a) Change oil and filter every 2,160 hours of operation or annually, whichever comes first, or perform an oil analysis at the same frequency in order to extend the oil change requirement. If the permittee chooses to use oil analysis in an effort to extend the oil/filter change requirement, the results of the analysis must verify the oil still meets the limits contained in (1)–(3) below. If any of these limits are exceeded, the oil must be changed within two business days of receiving the results of the analysis. If the engine is not in operation when the results are received, the oil must be changed within two business days or before commencing operation, whichever is later. The oil analysis program must be included in the engine’s maintenance plan required by Condition 3.B.17;
 - (1) The Total Acid Number increases by more than 3.0 milligrams of potassium hydroxide (KOH) per gram from the Total Acid Number when new.
 - (2) The viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new.
 - (3) The percent water content (by volume) is greater than 0.5.
- (b) Inspect spark plugs every 2,160 hours of operation or annually, whichever comes first; and
- (c) Inspect all hoses and belts every 2,160 hours of operation or annually, whichever comes first, and replace as necessary.

(Ref.: 40 CFR Part 63.6603(a), 40 CFR Part 63.6625(j), and Item 8 and Footnote 1 of Table 2d of 40 CFR Part 63, Subpart ZZZZ)

3.B.14 For Emission Points AB-008, AB-013, AB-018, AB-020, AB-023, and AB-024, the permittee shall comply with the following requirements:

- (a) Change oil and filter every 500 hours of operation or annually, whichever comes first, or perform an oil analysis at the same frequency in order to extend the oil change requirement. If the permittee chooses to use oil analysis in an effort to extend the oil/filter change requirement, the results of the analysis must verify the oil still meets the limits contained in (1)–(3) below. If any of these limits are exceeded, the oil must be changed within two business days of receiving the results of the analysis. If the engine is not in operation when the results are received, the oil must be changed within two business days or before commencing operation, whichever is later. The oil analysis program must be included in the engine’s maintenance plan required by Condition 3.B.17;

- (1) The Total Acid Number increases by more than 3.0 milligrams of potassium hydroxide (KOH) per gram from the Total Acid Number when new.
 - (2) The viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new.
 - (3) The percent water content (by volume) is greater than 0.5.
- (b) Inspect spark plugs every 1,000 hours of operation or annually, whichever comes first, and replace as necessary;
- (c) Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.

If the engine is operating during an emergency and it is not possible to shut down the engine in order to perform the work practices according to the schedule listed in (a)–(c) above, or if performing the work practice on the required schedule would otherwise pose an unacceptable risk under Federal, State, or local law, the work practice can be delayed until the emergency is over or the unacceptable risk under Federal, State, or local law has abated. The work practice should be performed as soon as practicable after the emergency has ended or the unacceptable risk under Federal, State, or local law has abated.

(Ref.: 40 CFR Part 63.6603(a), 40 CFR Part 63.6625(j), and Item 5 and Footnotes 1 and 2 of Table 2d of 40 CFR Part 63, Subpart ZZZZ)

3.B.15 For Emission Point AA-018, the permittee shall comply with the following requirements:

- (a) Change oil and filter every 500 hours of operation or annually, whichever comes first, or perform an oil analysis at the same frequency in order to extend the oil change requirement. If the permittee chooses to use oil analysis in an effort to extend the oil/filter change requirement, the results of the analysis must verify the oil still meets the limits contained in (1)–(3) below. If any of these limits are exceeded, the oil must be changed within two business days of receiving the results of the analysis. If the engine is not in operation when the results are received, the oil must be changed within two business days or before commencing operation, whichever is later. The oil analysis program must be included in the engine’s maintenance plan required by Condition 3.B.17;
- (1) Total Base Number is less than 30 percent of the Total Base Number of the oil when new.
 - (2) Viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new.

- (3) Percent water content (by volume) is greater than 0.5.
- (b) Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first, and replace as necessary;
- (c) Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.

If the engine is operating during an emergency and it is not possible to shut down the engine in order to perform the work practices according to the schedule listed in (a)–(c) above, or if performing the work practice on the required schedule would otherwise pose an unacceptable risk under Federal, State, or local law, the work practice can be delayed until the emergency is over or the unacceptable risk under Federal, State, or local law has abated. The work practice should be performed as soon as practicable after the emergency has ended or the unacceptable risk under Federal, State, or local law has abated.

(Ref.: 40 CFR Part 63.6603(a), 40 CFR Part 63.6625(i), and Item 4 and Footnotes 1 and 2 of Table 2d of 40 CFR Part 63, Subpart ZZZZ)

- 3.B.16 For Emission Points AA-001 through AA-003, AA-008, AA-018, and AB-001 through AB-005, AB-008, AB-013, AB-018, AB-020, AB-023, and AB-024, the permittee shall, at all times, be in compliance with the applicable requirements of 40 CFR Part 63, Subpart ZZZZ, and operate and maintain the engines, including associated monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require the permittee to make any further efforts to reduce emissions if levels required by Subpart ZZZZ have been achieved. Determination of whether such operation and maintenance procedures are being used will be based on information available to the MDEQ which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source. (Ref.: 40 CFR Part 63.6605)
- 3.B.17 For Emission Points AA-001 through AA-003, AA-008, AA-018, and AB-001 through AB-005, AB-008, AB-013, AB-018, AB-020, AB-023, and AB-024, the permittee shall operate and maintain each engine according to the manufacturer's emission-related written instructions or develop and follow a maintenance plan which provides to the extent practicable for the maintenance and operation of the engines in a manner consistent with good air pollution practice for minimizing emissions. (Ref.: 40 CFR Part 63.6625(e)(3) and Item 9 of Table 6 of 40 CFR Part 63, Subpart ZZZZ)
- 3.B.18 For Emission Points AA-018, AB-008, AB-013, AB-018, AB-020, AB-023, and AB-024, the permittee shall install and operate a non-resettable hour meter on each emergency engine. (Ref: 40 CFR Part 63.6625(f))

- 3.B.19 For Emission Points AA-018, AB-008, AB-013, AB-018, AB-020, AB-023, and AB-024, the permittee shall minimize each engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the non-startup emission limitations apply. (Ref.: 40 CFR Part 63.6625(h))
- 3.B.20 Emission Point AB-025 is subject to the Standards of Performance for Stationary Spark Ignition Internal Combustion Engines, 40 CFR Part 60, Subpart JJJJ. (Ref: 40 CFR Part 60.4230(a)(4)(iv))
- 3.B.21 For Emission Point AB-025, the permittee shall comply with the emission standards in 40 CFR Part 60.4231(c) over the entire life of the engine. (Ref.: 40 CFR Part 60.4233(c) and 40 CFR Part 60.4234)
- 3.B.22 For Emission Points AB-017 and AB-027, each regenerator still vent shall only be operated with emissions routed to the thermal oxidizer (Emission Point AB-028). (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))

- 3.B.23 For Emission Point AB-028, the permittee shall maintain the combustion zone temperature of the thermal oxidizer, according to the manufacturer's recommended specifications, at a minimum temperature of 1,300 degrees Fahrenheit. The permittee shall show, during an inspection by MDEQ, the combustion zone temperature of the thermal oxidizer. (Ref. 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))
- 3.B.24 For the collection of fugitive emission sources throughout the entire facility (Emission Point AB-031) and for the reciprocating compressor engines (Emission Points AB-029, and AB-030), the permittee is subject to the Standards of Performance for Crude Oil and Natural Gas Facilities for which Construction, Modification or Reconstruction Commenced After September 18, 2015, 40 CFR Part 60, Subpart OOOOa. (Ref. 40 CFR 60.5360a and 40 CFR 60.5365a(c) and (j), Subpart OOOOa)
- 3.B.25 For the collection of fugitive emission sources throughout the entire facility (Emission Point AB-031) and for the reciprocating compressor engines (Emission Points AB-029, and AB-030), the permittee shall:
- (a) Be in compliance with the applicable standards of 40 CFR 60, Subpart OOOOa upon startup of Emission Point AB-029 or AB-030, whichever is earliest, and
 - (b) At all times, including periods of startup, shutdown, and malfunction, maintain and operate any affected facility including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on information available to the DEQ which may include, but is not limited to, monitoring results, opacity observations, review of operating and maintenance procedures, and inspection of the source. The provisions for exemption from compliance during periods of startup, shutdown and malfunctions provided for in 40 CFR 60.8(c) do not apply to 40 CFR 60, Subpart OOOOa.

(Ref. 40 CFR 60.5370a (a) and (b), Subpart OOOOa)

C. Insignificant and Trivial Activity Emission Limitations & Standards

Applicable Requirement	Condition Number(s)	Pollutant/Parameter	Limit/Standard
11 Miss. Admin. Code Pt. 2, R. 1.3.D(1)(a).	3.C.1	PM	0.6 lbs/MMBTU
11 Miss. Admin. Code Pt. 2, R. 1.4.A(1).	3.C.2	SO ₂	4.8 lbs/MMBTU

3.C.1 The maximum permissible emission of ash and/or particulate matter from fossil fuel burning installations of less than 10 million BTU per hour heat input shall not exceed 0.6 pounds per million BTU per hour heat input. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.3.D(1)(a)).

3.C.2 The maximum discharge of sulfur oxides from any fuel burning installation in which the fuel is burned primarily to produce heat or power by indirect heat transfer shall not exceed 4.8 pounds (measured as sulfur dioxide) per million BTU heat input. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 1.4.A(1)).

There are no other requirements applicable to the insignificant activities listed in the source's Title V permit application

D. Work Practice Standards

Emission Point(s)	Applicable Requirement	Condition Number(s)	Pollutant/Parameter	Limit/Standard
FUG	40 CFR 60.5397a(a-g), Subpart OOOOa	3.D.1	VOC and Methane	Develop a fugitive emission monitoring plan
	40 CFR 60.5397a(h), Subpart OOOOa	3.D.2		Fugitive emission source repair or replacement requirements
	40 CFR 60.5425a and Table 3 to Subpart OOOOa	3.D.3		Applicability
AB-029 and AB-030	40 CFR 60.5385a(1)(a)-(b), Subpart OOOOa	3.D.4	VOC and Methane	Operational Requirement

3.D.1 For the collection of fugitive emission sources throughout the entire facility (FUG), the permittee shall demonstrate compliance with Subpart OOOOa by monitoring all fugitive emission components, as defined in 40 CFR 60.5430a. For the purposes of this condition, fugitive emissions are defined as: Any visible emission from a fugitive emissions component observed using optical gas imaging or an instrument reading of 500 ppm or greater using Method 21.

The permittee shall develop an emissions monitoring plan that covers the collection of fugitive emissions components within each company-defined area. This monitoring plan shall include the information specified in paragraphs (a) through (l) below:

- (a) The permittee shall conduct an initial monitoring survey within 60 days of the startup of Emission Point AB-029 or AB-030, whichever is earliest, as defined in 40 CFR 60.5430a, for each collection of fugitive emissions components at the compressor station. A monitoring survey shall be conducted at least quarterly after the initial survey. Consecutive quarterly monitoring surveys must be conducted at least 60 days apart. Each monitoring survey shall observe each fugitive emissions component, as defined in 40 CFR 60.5430a, for fugitive emissions.
- (b) The permittee shall specify the technique used in determining the presence of fugitive emissions (i.e. Method 21 from 40 CFR Part 60, Appendix A-7 or optical gas imaging).
- (c) The permittee shall include the manufacturer and model number of all fugitive emission detection equipment used.

- (d) The permittee shall include the procedures and timeframes for identifying and repairing fugitive emissions components from which fugitive emissions are detected. This includes timeframes for fugitive emission components that are unsafe to repair. At a minimum, the repair schedule shall meet the requirements of Condition 3.D.2.
- (e) The permittee shall include procedures and timeframes for verifying fugitive emission component repairs.
- (f) The permittee shall specify what records will be kept and the length of time these records will be kept.
- (g) If the permittee utilizes optical gas imaging, the monitoring plan shall include the information specified in (1) through (7) below:
 - (1) Verification that the optical gas imaging equipment is capable of imaging gases in the spectral range for the compound of highest concentration in the potential fugitive emissions. The optical gas imaging equipment must be capable of imaging a gas that is half methane, half propane at a concentration of 10,000 parts per million (ppm) at a flow rate of ≤ 60 grams per hour (g/hr) from a quarter inch diameter orifice. This verification is an initial verification and may either be performed by the facility, by the manufacturer, or by a third party. For the purposes of complying with the fugitives emissions monitoring program with optical gas imaging, a fugitive emission is defined as any visible emissions observed using optical gas imaging.
 - (2) Procedures for a daily verification check.
 - (3) Procedures for determining the permittee's maximum viewing distance from the equipment and procedures for how the permittee will ensure that this distance is maintained.
 - (4) Procedures for determining maximum wind speed during which monitoring can be performed and procedures for how the permittee will ensure monitoring occurs only at wind speeds below this threshold.
 - (5) Procedures for conducting surveys, including how the permittee will ensure an adequate thermal background is present in order to view potential fugitive emissions, how the permittee will deal with adverse monitoring conditions, such as wind, and how the permittee will deal with interferences (e.g., steam).
 - (6) Specification of the training and experience needed prior to performing surveys.

- (7) Procedures for calibration and maintenance. At a minimum, procedures must comply with those recommended by the manufacturer.

- (h) If the permittee utilizes Method 21 from 40 CFR Part 60, Appendix A-7, the monitoring plan shall include the information specified in subparagraphs (1) and (2) below. For the purposes of complying with the fugitive emissions monitoring program using Method 21 a fugitive emission is defined as an instrument reading of 500 ppm or greater.
 - (1) Verification that all monitoring equipment meets the requirements specified in Section 6.0 of Method 21 from 40 CFR Part 60, Appendix A-7. For purposes of instrument capability, the fugitive emissions definition shall be 500 ppm or greater methane using a FID-based instrument. If the permittee uses an analyzer other than a FID-based instrument, the permittee shall develop a site-specific fugitive emission definition that would be equivalent to 500 ppm methane using a FID-based instrument (e.g., 10.6 eV PID with a specified isobutylene concentration as the fugitive emission definition would provide equivalent response to your compound of interest).

 - (2) Procedures for conducting surveys. At a minimum, these procedures shall ensure that the surveys comply with the relevant sections of Method 21 from 40 CFR Part 60, Appendix A-7, including Section 8.3.1.

The monitoring plan shall also include the information specified in paragraphs (i) through (l) below:

- (i) A site map.

- (j) A defined observation path that ensures that all fugitive emissions components are within sight of the path. The observation path must account for interferences.

- (k) If the permittee utilizes Method 21, the plan shall also include a list of fugitive emissions components to be monitored and the method for determining location of fugitive emissions components to be monitored in the field (e.g. tagging, identification on a process and instrumentation diagram, etc.).

- (l) The plan shall also include the written plan developed for all of the fugitive emission components designated as difficult-to-monitor in accordance with 40 CFR 60.5397(g)(3)(i) and the written plan for fugitive emission components designated as unsafe-to-monitor in accordance with 40 CFR 60.5397(g)(3)(ii).

(Ref.: 40 CFR 60.5397a(a-g) Subpart OOOOa)

- 3.D.2 For the collection of fugitive emission sources throughout the entire facility (FUG), each identified source of fugitive emissions shall be repaired or replaced in accordance with paragraphs (a) through (c) below:
- (a) Each identified source of fugitive emissions shall be repaired or replaced as soon as practicable, but no later than 30 calendar days after detection of the fugitive emissions.
 - (b) If the repair or replacement is technically infeasible, would require a vent blowdown or a compressor station shutdown, or would be unsafe to repair during operation of the unit, the repair or replacement must be completed during the next scheduled compressor station shutdown, after a planned vent blowdown or within 2 years, whichever is earlier.
 - (c) Each repaired or replaced fugitive emissions component must be resurveyed as soon as practicable, but no later than 30 days after being repaired, to ensure that there are no fugitive emissions. This survey shall comply with the requirements of subparagraphs (i) through (iv), as applicable:
 - (1) For repairs that cannot be made during the monitoring survey when the fugitive emissions are initially found, the operator may resurvey the repaired fugitive emissions components using either Method 21 or optical gas imaging within 30 days of finding such fugitive emissions.
 - (2) For each repair that cannot be made during the monitoring survey when the fugitive emissions are initially found, a digital photograph must be taken of that component or the component must be tagged for identification purposes. The digital photograph must include the date that the photograph was taken, must clearly identify the component by location within the site (e.g., the latitude and longitude of the component or by other descriptive landmarks visible in the picture).
 - (3) If the permittee utilizes Method 21 to resurvey the repaired fugitive emissions components, then the fugitive emissions component is considered repaired when the Method 21 instrument indicates a concentration of less than 500 ppm above background or when no soap bubbles are observed when the alternative screening procedures specified in Section 8.3.3 of Method 21 are used. The permittee shall utilize the Method 21 monitoring requirements specified in Condition 3.D.1(h)(2) or the alternative screening procedures specified in Section 8.3.3 of Method 21.
 - (4) If the permittee utilizes optical gas imaging to resurvey the repaired fugitive emissions components, then the fugitive emissions component is considered repaired when the optical gas imaging instrument shows no indication of visible

emissions. The permittee shall utilize the optical gas monitoring requirements specified in Condition 3.D.1(g).

(Ref.: 40 CFR 60.5397a(h) Subpart OOOOa)

- 3.D.3 For the collection of fugitive emission sources throughout the entire facility (Emission Point AB-031), the permittee must comply with the General Provisions of 40 CFR 60.1 through 40 CFR 60.19 except for 40 CFR 60.11. (Ref.: 40 CFR 60.5425a and Table 3 to Subpart OOOOa)
- 3.D.4 For Emission Points AB-029 and AB-030, the permittee shall replace the reciprocating compressor rod packing on or before the compressor has operated for 26,000 hours or replace the compressor rod packing prior to 36 months from the date of the most recent rod packing replacement, or 36 months from the date of startup for a new reciprocating compressor for which the rod packing has not yet been replaced.

(Ref.: 40 CFR 60.5385a(1)(a)-(b), Subpart OOOOa)

SECTION 4. COMPLIANCE SCHEDULE

- 4.1 Unless otherwise specified herein, the permittee shall be in compliance with all requirements contained herein upon issuance of this permit.
- 4.2 Except as otherwise specified herein, the permittee shall submit to the Permit Board and to the Administrator of EPA Region IV a certification of compliance with permit terms and conditions, including emission limitations, standards, or work practices, by January 31 for the preceding calendar year. Each compliance certification shall include the following:
- (a) the identification of each term or condition of the permit that is the basis of the certification;
 - (b) the compliance status;
 - (c) whether compliance was continuous or intermittent;
 - (d) the method(s) used for determining the compliance status of the source, currently and over the applicable reporting period;
 - (e) such other facts as may be specified as pertinent in specific conditions elsewhere in this permit.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.C(5)(a), (c), & (d).)

- 4.3 The permittee shall submit progress reports consistent with an applicable schedule of compliance and 11 Miss. Admin. Code Pt. 2, R. 6.2.C(8). semiannually, or at such other frequency as is specified in an applicable requirement or by the Permit Board. Such progress reports shall contain the following:
- (a) dates for achieving the activities, milestone(s), or compliance required in the schedule of compliance, and dates when such activities, milestone(s) or compliance were achieved; and
 - (b) an explanation of why any dates in the schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.2.C(8).)

SECTION 5. MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS

A. General Monitoring, Recordkeeping and Reporting Requirements

5.A.1 The permittee shall install, maintain, and operate equipment and/or institute procedures as necessary to perform the monitoring and recordkeeping specified below. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3).)

5.A.2 In addition to the recordkeeping specified below, the permittee shall include with all records of required monitoring information the following:

- (a) the date, place as defined in the permit, and time of sampling or measurements;
- (b) the date(s) analyses were performed;
- (c) the company or entity that performed the analyses;
- (d) the analytical techniques or methods used;
- (e) the results of such analyses; and
- (f) the operating conditions existing at the time of sampling or measurement.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(b)(1).)

5.A.3 Except where a longer duration is specified in an applicable requirement, the permittee shall retain records of all required monitoring data and support information for a period of at least five (5) years from the date of the monitoring sample, measurement, report, or application. Support information includes all calibration and maintenance records, all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by the permit. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(b)(2).)

5.A.4 Except as otherwise specified herein, the permittee shall submit reports of any required monitoring by July 31 and January 31 for the preceding six-month period. All instances of deviations from permit requirements must be clearly identified in such reports and all required reports must be certified by a responsible official consistent with 11 Miss. Admin. Code Pt. 2, R. 6.2.E. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(c)(1).)

5.A.5 Except as otherwise specified herein, the permittee shall report all deviations from permit requirements, including those attributable to upsets, the probable cause of such deviations, and any corrective actions or preventive measures taken. Said report shall be made within

five (5) days of the time the deviation began. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(c)(2).)

- 5.A.6 Except as otherwise specified herein, the permittee shall perform emissions sampling and analysis in accordance with EPA Test Methods and with any continuous emission monitoring requirements, if applicable. All test methods shall be those versions or their equivalents approved by the DEQ and the EPA. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3).)
- 5.A.7 The permittee shall maintain records of any alterations, additions, or changes in equipment or operation. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3).)

B. Specific Monitoring and Recordkeeping Requirements

Emission Point(s)	Applicable Requirement	Condition Number	Pollutant / Parameter Monitored	Monitoring/Recordkeeping Requirement
AA-001 through AA-003, AA-008, and AB-001 through AB-005	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	5.B.1	Hours	Operational records
	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	5.B.2	NO _x and CO	Keep records of emissions
	40 CFR Part 63.6603(f)	5.B.3	Area Source HAPs	Monitor and keep records of remote evaluations
AA-001 through AA-003	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	5.B.4	NO _x and CO	Conduct performance tests
AA-008	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	5.B.5	NO _x and CO	Conduct performance tests
AB-001 through AB-005	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	5.B.6	NO _x and CO	Conduct performance tests
AA-001 through AA-003, AA-008, AA-018, and AB-001 through AB-005, AB-008, AB-013, AB-018, AB-020, AB-023, and AB-024	40 CFR Part 63.6655(e)(2) and (3)	5.B.7	Area Source HAPs	Keep records of the maintenance
	40 CFR Part 63.6660(1)-(3)	5.B.8	Area Source HAPs	General recordkeeping requirement
AA-018, AB-008, AB-013, AB-018, AB-020, AB-023, AB-024, and AB-025	40 CFR Part 63.6655(f) and 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	5.B.9	Hours	Monitor and keep records of hours of and reason for operation
AA-018, AB-008, AB-013, AB-018, AB-020, AB-023, and AB-024	40 CFR Part 63.6640(f) and 40 CFR Part 63.6675	5.B.10	General Operating Condition	Emergency operational requirements

Emission Point(s)	Applicable Requirement	Condition Number	Pollutant / Parameter Monitored	Monitoring/Recordkeeping Requirement
AB-025	40 CFR Part 60.4243(d) and 40 CFR Part 60.4248	5.B.11	General Operating Condition	Emergency operational requirements
	40 CFR Part 60.4243(a)(1) and (2)(i)	5.B.12	NO _x , CO, and VOC	Compliance Demonstration
	40 CFR Part 60.4245(a)(1)-(4)	5.B.13	NO _x , CO, and VOC	Records
AB-028	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	5.B.14	Temperature	Monitoring and recordkeeping requirements
AB-031	40 CFR 60.5410a(j), Subpart OOOOa	5.B.15	VOC	Initial Compliance Demonstration
	40 CFR 60.5415a(h), Subpart OOOOa	5.B.16		Continuous Compliance Demonstration
	40 CFR 60.5420a(c), Subpart OOOOa	5.B.17		Recordkeeping requirements
AB-029 and AB-030	40 CFR 60.5385a(1), (b), and (c) Subpart OOOOa, 40 CFR 60.5410a(c)(1), Subpart OOOOa and 40 CFR 60.5415a(c)(1), Subpart OOOOa	5.B.18	Hours	Monitoring requirements
	40 CFR 60.5420a(c)(3)(i)-(iii), Subpart OOOOa and	5.B.19	General Operating Condition	Operational requirements

5.B.1 For Emission Points AA-001, AA-002, AA-003, AA-008, AB-001, AB-002, AB-003, AB-004, and AB-005, the permittee shall keep records of the hours of operation of each engine on a monthly and 12-month consecutive rolling total basis. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))

5.B.2 For Emission Points AA-001, AA-002, AA-003, AA-008, AB-001, AB-002, AB-003, AB-004 and AB-005, the permittee shall demonstrate compliance with the NO_x and CO tons/year limitations by the following calculations:

$$\text{TPY of NO}_x = 10.38 * (\text{hours of operation of AA-001, AA-002 \& AA-003}) + 5.93 * (\text{hours of operation of AA-008}) + 5.11 * (\text{hours of operation of AB-001, AB-002, AB-003, AB-004 and AB-005})$$

$$\text{TPY of CO} = 12.83 * (\text{hours of operation of AA-001, AA-002 \& AA-003}) + 7.33 * (\text{hours of operation of AA-008}) + 10.35 * (\text{hours of operation of AB-001, AB-002, AB-003, AB-004 and AB-005})$$

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))

- 5.B.3 For Emission Points AA-001 through AA-003, AA-008, and AB-001 through AB-005, the permittee must evaluate the status of each stationary RICE every 12 months and keep records of the initial and annual evaluation of the status of each engine. If the evaluation indicates that the stationary RICE no longer meets the definition of remote stationary RICE in 40 CFR Part 63.6675, the permittee must comply with all of the requirements for existing non-emergency SI 4SLB stationary RICE with a site rating of more than 500 HP located at area sources of HAP that are not remote stationary RICE within 1 year of the evaluation. Records of each remote evaluation must be maintained for a period of at least five (5) years. (Ref.: 40 CFR Part 63.6603(f))
- 5.B.4 For Emission Points AA-001, AA-002, and AA-003, the permittee shall conduct annual performance tests on one engine to demonstrate compliance with the NO_x and CO lb/hr limitations. The tests shall be done using a portable analyzer for NO_x and CO in accordance with ASTM D6522-00, or as an option the permittee may use EPA Reference Methods 7 and 10 or other approved equivalents

The NO_x and CO testing shall be performed simultaneously and while the engine is operating at peak load conditions. The permittee shall conduct an annual performance test on one engine. Each engine shall be tested on a rotating annual basis. The performance test shall be conducted by December 31 of each calendar year. If the scheduled unit is not operating during the scheduled performance test, the permittee may request MDEQ to specify another similar unit for performance testing.

The permittee shall submit a test protocol at least thirty (30) days prior to the scheduled test date to ensure that all test methods and procedures are acceptable to the DEQ. The DEQ must be notified at least ten (10) days prior to the scheduled test date so that an observer may be scheduled to witness the test(s). After the first successful submittal of a written test protocol for the portable analyzers, the permittee may request that the resubmittal of testing protocol be waived for subsequent testing by certifying in writing at least thirty (30) days prior to subsequent testing that all conditions for testing remain unchanged such that the original protocol can and will be followed.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))

- 5.B.5 For Emission Point AA-008, the permittee shall conduct annual performance tests on the engine to demonstrate compliance with the NO_x and CO lb/hr limitations. The tests shall be done using a portable analyzer for NO_x and CO in accordance with ASTM D6522-00, or as an option the permittee may use EPA Reference Methods 7 and 10 or other approved equivalents.

The NO_x and CO testing shall be performed simultaneously and while the engine is operating at peak load condition. The performance test shall be conducted by December 31 of each calendar year.

The permittee shall submit a test protocol at least thirty (30) days prior to the scheduled test date to ensure that all test methods and procedures are acceptable to the DEQ. The DEQ must be notified at least ten (10) days prior to the scheduled test date so that an observer may be scheduled to witness the test(s). After the first successful submittal of a written test protocol for the portable analyzers, the permittee may request that the resubmittal of testing protocol be waived for subsequent testing by certifying in writing at least thirty (30) days prior to subsequent testing that all conditions for testing remain unchanged such that the original protocol can and will be followed.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))

- 5.B.6 For Emission Points AB-001 through AB-005, the permittee shall conduct annual performance tests on one engine to demonstrate compliance with the NO_x and CO lb/hr limitations. The tests shall be done using a portable analyzer for NO_x and CO in accordance with ASTM D6522-00, or as an option the permittee may use EPA Reference Methods 7 and 10 or other approved equivalents.

The NO_x and CO testing shall be performed simultaneously and while the engine is operating at peak load condition. The permittee shall conduct an annual performance test on one engine. Each engine shall be tested on a rotating annual basis. The performance test shall be conducted by December 31 of each calendar year. If the scheduled unit is not operating during the scheduled performance test, the permittee can request MDEQ to specify another similar unit for performance testing.

The permittee shall submit a test protocol at least thirty (30) days prior to the scheduled test date to ensure that all test methods and procedures are acceptable to the DEQ. The DEQ must be notified at least ten (10) days prior to the scheduled test date so that an observer may be scheduled to witness the test(s). After the first successful submittal of a written test protocol for the portable analyzers, the permittee may request that the resubmittal of testing protocol be waived for subsequent testing by certifying in writing at least thirty (30) days prior to subsequent testing that all conditions for testing remain unchanged such that the original protocol can and will be followed.

(Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))

- 5.B.7 For Emission Points AA-001 through AA-003, AA-008, AA-018, AB-001 through AB-005, AB-008, AB-013, AB-018, AB-020, AB-023 and AB-024, the permittee must keep records of the maintenance conducted on the stationary RICE in order to demonstrate that the stationary RICE and after-treatment control device (if any) were operated and maintained according to the permittee's maintenance plan. (40 CFR Part 63.6655(e)(2) and (3))
- 5.B.8 For Emission Points AA-001 through AA-003, AA-008, AA-018, AB-001 through AB-005, AB-008, AB-013, AB-018, AB-020, AB-023 and AB-024, the permittee must keep records in a form suitable and readily available for expeditious review according to 40 CFR Part 63.10(b)(1). Each record must be kept for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record. Each record must be kept readily accessible in hard copy or electronic form for at least 5 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record, according to 40 CFR Part 63.10(b)(1). (40 CFR Part 63.6660(1)-(3))
- 5.B.9 For Emission Points AA-018, AB-008, AB-013, AB-018, AB-020, AB-023, AB-024, and AB-025, the permittee shall keep records of the hours of operation of the engine recorded using each engine's non-resettable hour meter. These records must indicate how many hours are spent in emergency operation, including what classified the operation as an emergency, and how many hours are spent in nonemergency operation. Records should also include any time spent operating for the purposes identified in Permit Conditions 5.B.10(b) and (c) and 5.B.11(b) and (c), and should contain an explanation of the emergency situation, date, and start and end time of engine operation for this purpose. (Ref.: 40 CFR Part 63.6655(f) and 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))
- 5.B.10 For Emission Points AA-018, AB-008, AB-013, AB-018, AB-020, AB-023, and AB-024, the permittee shall operate the emergency engine according to the requirements below:
- (a) There is no limit on the use of the engine during emergency situations.
 - (b) The engine may be operated for a maximum of 100 hours per calendar year for maintenance checks and readiness testing, provided that the tests are recommended by federal, state, or local government, the manufacturer, the vendor, the regional transmission organization or equivalent balancing authority and transmission operator, or the insurance company associated with the engine. The permittee may petition the MDEQ for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the permittee maintains records indicating that federal, state, or local standards require maintenance and testing of emergency RICE beyond 100 hours per calendar year. Any operation for non-emergency situations as allowed by paragraph (c) counts as part of the 100 hours per calendar year allowed by this paragraph.
 - (c) The engine may be operated for up to 50 hours per calendar year in non-emergency

situations. The 50 hours of operation in non-emergency situations are counted as part of the 100 hours per calendar year for maintenance and testing. The 50 hours per year for non-emergency situations cannot be used for peak shaving or non-emergency demand response, or to generate income for a facility to supply power to an electric grid or otherwise supply power as part of a financial arrangement with another entity.

If the emergency engine is not operated according to the requirements in (a) - (c) above, the engine will not be considered an emergency engine under this subpart and will need to meet any applicable requirements for a non-emergency engine. (Ref.: 40 CFR Part 63.6640(f) and 63.6675)

5.B.11 For Emission Point AB-025, the permittee shall operate the emergency engine according to the requirements below:

- (a) There is no limit on the use of the engine during emergency situations.
- (b) The engine may be operated for a maximum of 100 hours per calendar year for maintenance checks and readiness testing, provided that the tests are recommended by federal, state, or local government, the manufacturer, the vendor, the regional transmission organization or equivalent balancing authority and transmission operator, or the insurance company associated with the engine. The permittee may petition the MDEQ for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the permittee maintains records indicating that federal, state, or local standards require maintenance and testing of emergency RICE beyond 100 hours per calendar year. Any operation for non-emergency situations as allowed by paragraph (c) counts as part of the 100 hours per calendar year allowed by this paragraph.
- (c) The engine may be operated for up to 50 hours per calendar year in non-emergency situations. The 50 hours of operation in non-emergency situations are counted as part of the 100 hours per calendar year for maintenance and testing. The 50 hours per year for non-emergency situations cannot be used for peak shaving or non-emergency demand response, or to generate income for a facility to supply power to an electric grid or otherwise supply power as part of a financial arrangement with another entity.

If the emergency engine is not operated according to the requirements in (a) - (c) above, the engine will not be considered an emergency engine under this subpart and will need to meet any applicable requirements for a non-emergency engine. (Ref.: 40 CFR Part 60.4243(d) and 60.4248)

5.B.12 For Emission Point AB-025, the permittee shall comply with emission standards cited in Condition 3.B.21 by purchasing an engine certified to the emission standards in 40 CFR Part 60.4231(c), as applicable, for the same engine class and maximum engine power. In addition, the permittee must meet one of the requirements specified below:

- (a) If the certified stationary SI internal combustion engine and control device is operated and maintained according to the manufacturer's emission-related written instructions, records must be kept of conducted maintenance to demonstrate compliance, but no performance testing is required by the permittee. The permittee must also meet the applicable requirements as specified in 40 CFR Part 1068, Subparts A through D. If the engine settings are adjusted according to and consistent with the manufacturer's instructions, the stationary SI internal combustion engine will not be considered out of compliance.
- (b) If the certified stationary SI internal combustion engine and control device are not operated and maintained according to the manufacturer's emission-related written instructions, the engine will be considered a non-certified engine, and compliance shall be demonstrated by keeping a maintenance plan and records of conducted maintenance to demonstrate compliance and, to the extent practicable, the permittee must maintain and operate the engine in a manner consistent with good air pollution control practice for minimizing emissions, but no performance testing is required by the permittee.

(40 CFR Part 60.4243(a)(1) and (2)(i))

5.B.13 For Emission Point AB-025, the permittee shall keep records of the following information:

- (a) All notifications submitted to comply with Subpart JJJJ and all documentation supporting any notification;
- (b) Maintenance conducted on the engine;
- (c) If the emergency engine is a certified engine, documentation from the manufacturer that the engine is certified to meet the emission standards and information as required in 40 CFR parts 90, 1048, 1054, and 1060, as applicable; and
- (d) Documentation that the engine meets the emission standards.
- (e) If the emergency engine does not meet the standards applicable to non-emergency engines, the permittee must keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. The permittee must document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation.

(Ref: 40 CFR Part 60.4245(a)(1)-(4) and (b))

- 5.B.14 For Emission Point AB-028, the permittee shall monitor the combustion zone temperature of the thermal oxidizer whenever gas is being dehydrated in Emission Point AB-017 and/or AB-027. A record of the daily average combustion zone temperature shall be maintained for any day when gas is being dehydrated in Emission Points AB-017 and/or AB-027. (Ref. 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))
- 5.B.15 For the collection of fugitive emission sources throughout the entire facility (Emission Point AB-031), the permittee shall demonstrate initial compliance with the fugitive emission standards for each collection of fugitive emissions components at the compressor station by complying with the requirements of paragraphs (a) through (e) below. The initial compliance period begins upon initial startup of Emission Point AB-029 or AB-030, and ends no later than one (1) year after the initial startup date. The initial compliance period may be less than one full year.
- (a) The permittee shall develop a fugitive emissions monitoring plan as required in Condition 3.D.1.
 - (b) The permittee shall conduct an initial monitoring survey as required in Condition 3.D.1(a).
 - (c) The permittee shall maintain the records specified in Condition 5.B.17.
 - (d) The permittee shall repair each identified source of fugitive emissions for each affected facility as required in Condition 3.D.2.
 - (e) The permittee shall submit the initial annual report for the collection of fugitive emissions components at the site as required in Condition 5.C.6.

(Ref.: 40 CFR 60.5410a(j), Subpart OOOOa)

- 5.B.16 For the collection of fugitive emission sources throughout the entire facility (Emission Point AB-031), the permittee shall demonstrate continuous compliance with the fugitive emission standards for each collection of fugitive emissions components at the compressor station by complying with the requirements of paragraphs (a) through (d) below:
- (a) The permittee shall conduct periodic monitoring surveys as required in Condition 3.D.1(a).
 - (b) The permittee shall repair or replace each identified source of fugitive emissions as required in Condition 3.D.2.

- (c) The permittee shall maintain the records specified in Condition 5.B.17.
- (d) The permittee shall submit annual reports for the collection of fugitive emissions components at the compressor station as required in Condition 5.C.6.

(Ref.: 40 CFR 60.5415a(h), Subpart OOOOa)

5.B.17 For the collection of fugitive emission sources throughout the entire facility (Emission Point AB-031), the permittee shall maintain the records identified in 40 CFR 60.7(f) and 40 CFR 60.5420a(c)(15). All required records must be maintained either on-site or at the nearest local field office for at least five (5) years. Any required records which are submitted electronically via EPA's CDX may be maintained in electronic format.

(Ref.: 40 CFR 60.5397(i) and 40 CFR 60.5420a(c), Subpart OOOOa)

5.B.18 For Emission Points AB-029 and AB-030, the permittee shall continuously monitor the number of hours of operation or track the number of months since initial startup or the date of the most recent rod packing replacement, whichever is later.

(Ref.: 40 CFR 60.5385a(1), (b), and (c), 40 CFR 60.5410a(c)(1), and 40 CFR 60.5415a(c)(1), Subpart OOOOa)

5.B.19 For Emission Points AB-029 and AB-030, the permittee shall maintain the following records:

- (a) Records of the cumulative number of hours of operation or number of months since initial startup or the previous replacement of the reciprocating compressor rod packing, whichever is later,
- (b) Records of the date and time of each reciprocating compressor rod packing replacement, and
- (c) Records of deviations in cases where the reciprocating compressor was not operated in compliance with the requirements specified in Condition 3.D.4.

(Ref.: 40 CFR 60.5420a(c)(3)(i)-(iii), Subpart OOOOa)

C. Specific Reporting Requirements

Emission Point(s)	Applicable Requirement	Condition Number	Pollutant / Parameter Monitored	Reporting Requirement
AA-001, AA-002, AA-003, AA-008, and AB-001, through AB-005	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	5.C.1	Hours	Submit semiannual reports of operations
AA-001 through AA-003	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	5.C.2	NO _x and CO	Submit portable analyzer test results
AA-008	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	5.C.3	NO _x and CO	Submit portable analyzer test results
AB-001 through AB-005	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	5.C.4	NO _x and CO	Submit portable analyzer test results
AB-028	11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2)	5.C.5	Temperature	Submit semiannual reports of operations
AB-031	40 CFR 60.5420a(b), Subpart OOOOa	5.C.6	VOC	Submit annual reports
AB-029 and AB-030		5.C.7		

- 5.C.1 For Emission Points AA-001, AA-002, AA-003, AA-008, and AB-001 through AB-005, the permittee shall submit semiannual reports of the monthly hours of operation of each source for the previous 12-month period in accordance with Condition 5.A.4. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))
- 5.C.2 For Emission Points AA-001, AA-002, and AA-003, the permittee shall submit the results of each performance test required in Condition 5.B.4 within 30 days after the test has been completed. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))
- 5.C.3 For Emission Point AA-008, the permittee shall submit the results of each performance test required in Condition 5.B.5 within 30 days after the test has been completed. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))
- 5.C.4 For Emission Points AB-001 through AB-005, the permittee shall submit the results of each performance test required in Condition 5.B.6 within 30 days after the test has been completed. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))

- 5.C.5 For Emission Point AB-028, the permittee shall submit semiannual reports of the combustion zone temperature for the previous 6-month period in accordance with Condition 5.A.4. (Ref.: 11 Miss. Admin. Code Pt. 2, R. 6.3.A(3)(a)(2))
- 5.C.6 For the collection of fugitive emission sources throughout the entire facility (Emission Point AB-031), the permittee shall submit annual reports containing the information specified in 40 CFR 60.5420a(b)(1), (b)(7), and (b)(11). The initial annual report is due no later than 90 days after the end of the initial compliance period as determined according to Condition 5.B.15. Subsequent annual reports are due no later than same date each year as the initial annual report. If the permittee owns or operates more than one affected facility, the permittee may submit one report for multiple affected facilities provided the report contains all of the information required as specified in 40 CFR 60.5420a(b)(1) through (b)(8), as applicable, except as provided in 40 CFR 60.5420a(b)(13).

The permittee must submit reports to the EPA via the CEDRI. (CEDRI can be accessed through the EPA's CDX (<https://cdx.epa.gov/>.) The permittee must use the appropriate electronic report in CEDRI for this subpart or an alternate electronic file format consistent with the extensible markup language (XML) schema listed on the CEDRI Web site (<https://www3.epa.gov/ttn/chief/cedri/>). If the reporting form specific to this subpart is not available in CEDRI at the time that the report is due, you must submit the report to the Administrator at the appropriate address listed in 40 CFR 60.4. Once the form has been available in CEDRI for at least 90 calendar days, the permittee must begin submitting all subsequent reports via CEDRI. The reports must be submitted by the deadlines specified 40 CFR Part 60 Subpart OOOOa regardless of the method in which the reports are submitted.

(Ref.: 40 CFR 60.5420a(b)(1), (7) and (11), Subpart OOOOa)

- 5.C.7 For Emission Points AB-029 and AB-030, the permittee shall submit annual reports containing the information specified below. The initial annual report is due no later than 90 days after the end of the initial compliance period as determined according to Condition 5.B.15. Subsequent annual reports are due no later than same date each year as the initial annual report. If the permittee owns or operates more than one affected facility, the permittee may submit one report for multiple affected facilities provided the report contains all of the information required as specified in 40 CFR 60.5420a(b)(1) through (b)(8), as applicable, except as provided in 40 CFR 60.5420a(b)(13).
- (a) The company name, facility site name associated with the affected facility and address of the affected facility.
 - (b) An identification of each affected facility being included in the annual report.
 - (c) Beginning and ending dates of the reporting period.
 - (d) A certification by a certifying official of truth, accuracy, and completeness. This

certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

- (e) The cumulative number of hours of operation or the number of months since initial startup or since the previous reciprocating compressor rod packing replacement, whichever is later.
- (f) Records of the deviations specified in Condition 5.B.19(c) that occurred during the reporting period.

The permittee must submit reports to the EPA via the CEDRI. (CEDRI can be accessed through the EPA's CDX (<https://cdx.epa.gov/>.) The permittee must use the appropriate electronic report in CEDRI for this subpart or an alternate electronic file format consistent with the extensible markup language (XML) schema listed on the CEDRI Web site (<https://www3.epa.gov/ttn/chief/cedri/>). If the reporting form specific to this subpart is not available in CEDRI at the time that the report is due, you must submit the report to the Administrator at the appropriate address listed in 40 CFR 60.4. Once the form has been available in CEDRI for at least 90 calendar days, the permittee must begin submitting all subsequent reports via CEDRI. The reports must be submitted by the deadlines specified 40 CFR Part 60 Subpart OOOOa regardless of the method in which the reports are submitted.

(Ref.: 40 CFR 60.5420a(b)(1), (4) and (11), Subpart OOOOa)

SECTION 6. ALTERNATIVE OPERATING SCENARIOS

6.1 None permitted.

SECTION 7. TITLE VI REQUIREMENTS

The following are applicable or potentially applicable requirements originating from Title VI of the Clean Air Act – Stratospheric Ozone Protection. The full text of the referenced regulations may be found on-line at <http://www.ecfr.gov/> under Title 40, or DEQ shall provide a copy upon request from the permittee.

- 7.1 If the permittee produces, transforms, destroys, imports or exports a controlled substance or imports or exports a controlled product, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart A – Production and Consumption Controls.
- 7.2 If the permittee performs service on a motor vehicle for consideration when this service involves the refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart B – Servicing of Motor Vehicle Air Conditioners.
- 7.3 The permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart E – The Labeling of Products Using Ozone-Depleting Substances, for the following containers and products:
 - (a) All containers in which a class I or class II substance is stored or transported;
 - (b) All products containing a class I substance; and
 - (c) All products directly manufactured with a process that uses a class I substance, unless otherwise exempted by this subpart or, unless EPA determines for a particular product that there are no substitute products or manufacturing processes for such product that do not rely on the use of a class I substance, that reduce overall risk to human health and the environment, and that are currently or potentially available. If the EPA makes such a determination for a particular product, then the requirements of this subpart are effective for such product no later than January 1, 2015.
- 7.4 If the permittee performs any of the following activities, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart F – Recycling and Emissions Reduction:
 - (a) Servicing, maintaining, or repairing appliances;
 - (b) Disposing of appliances, including small appliances and motor vehicle air conditioners; or
 - (c) Refrigerant reclaimers, technician certifying programs, appliance owners and operators, manufacturers of appliances, manufacturers of recycling and recovery equipment, approved recycling and recovery equipment testing organizations, persons

selling class I or class II refrigerants or offering class I or class II refrigerants for sale, and persons purchasing class I or class II refrigerants.

- 7.5 The permittee shall be allowed to switch from any ozone-depleting substance to any acceptable alternative that is listed in the Significant New Alternatives Policy (SNAP) program promulgated pursuant to 40 CFR Part 82, Subpart G – Significant New Alternatives Policy Program. The permittee shall also comply with any use conditions for the acceptable alternative substance.
- 7.6 If the permittee performs any of the following activities, the permittee shall comply with the applicable requirements of 40 CFR Part 82, Subpart H – Halon Emissions Reduction:
- (a) Any person testing, servicing, maintaining, repairing, or disposing of equipment that contains halons or using such equipment during technician training;
 - (b) Any person disposing of halons;
 - (c) Manufacturers of halon blends; or
 - (d) Organizations that employ technicians who service halon-containing equipment.

APPENDIX A

List of Abbreviations Used In this Permit

11 Miss. Admin. Code Pt. 2, Ch. 1.	Air Emission Regulations for the Prevention, Abatement, and Control of Air Contaminants
11 Miss. Admin. Code Pt. 2, Ch. 2.	Permit Regulations for the Construction and/or Operation of Air Emissions Equipment
11 Miss. Admin. Code Pt. 2, Ch. 3.	Regulations for the Prevention of Air Pollution Emergency Episodes
11 Miss. Admin. Code Pt. 2, Ch. 4.	Ambient Air Quality Standards
11 Miss. Admin. Code Pt. 2, Ch. 5.	Regulations for the Prevention of Significant Deterioration of Air Quality
11 Miss. Admin. Code Pt. 2, Ch. 6.	Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Clean Air Act
11 Miss. Admin. Code Pt. 2, Ch. 7.	Acid Rain Program Permit Regulations for Purposes of Title IV of the Federal Clean Air Act
BACT	Best Available Control Technology
CEM	Continuous Emission Monitor
CEMS	Continuous Emission Monitoring System
CFR	Code of Federal Regulations
CO	Carbon Monoxide
COM	Continuous Opacity Monitor
COMS	Continuous Opacity Monitoring System
DEQ	Mississippi Department of Environmental Quality
EPA	United States Environmental Protection Agency
gr/dscf	Grains Per Dry Standard Cubic Foot
HP	Horsepower
HAP	Hazardous Air Pollutant
lbs/hr	Pounds per Hour
M or K	Thousand
MACT	Maximum Achievable Control Technology
MM	Million
MMBTUH	Million British Thermal Units per Hour
NA	Not Applicable
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emissions Standards for Hazardous Air Pollutants, 40 CFR 61 or National Emission Standards for Hazardous Air Pollutants for Source Categories, 40 CFR 63
NM VOC	Non-Methane Volatile Organic Compounds
NO _x	Nitrogen Oxides
NSPS	New Source Performance Standards, 40 CFR 60
O&M	Operation and Maintenance
PM	Particulate Matter
PM ₁₀	Particulate Matter less than 10 µm in diameter
ppm	Parts per Million
PSD	Prevention of Significant Deterioration, 40 CFR 52
SIP	State Implementation Plan
SO ₂	Sulfur Dioxide
TPY	Tons per Year
TRS	Total Reduced Sulfur
VEE	Visible Emissions Evaluation
VHAP	Volatile Hazardous Air Pollutant
VOC	Volatile Organic Compound

APPENDIX B

LIST OF REGULATIONS REFERENCED IN PERMIT

The full text of the regulations referenced in this permit may be found on-line at <http://www.deq.state.us.us> and <http://ecfr.gpoaccess.gov>, or the Mississippi Department of Environmental Quality (MDEQ) will provide a copy upon request. A list of regulations referenced in this permit is shown below:

11 Miss. Admin. Code Pt. 2, Ch. 1, Mississippi Air Emission Regulations for the Prevention, Abatement, and Control of Air Contaminants (Amended December 14, 2011)

11 Miss. Admin. Code Pt. 2, Ch. 6, Mississippi Air Emissions Operating Permit Regulations for the Purposes of Title V of the Federal Air Emissions Operating Permit Regulations for the Purpose of Title V of the Federal Clean Air Act (Amended December 14, 2011)

40 CFR Part 82 — Title VI of the Clean Air Act (Stratospheric Ozone Protection)

40 CFR Part 63, Subpart A – General Provisions

40 CFR Part 63, Subpart ZZZZ — National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

40 CFR Part 60, Subpart A – General Provisions

40 CFR Part 60, Subpart JJJJ — Standards of Performance for Stationary Spark Ignition Internal Combustion Engines

Subpart OOOOa — Standards of Performance for Crude Oil and Natural Gas Facilities for which Construction, Modification or Reconstruction Commenced After September 18, 2015